

**ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.29**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	ILS: DA LOC: 5.41 NM AFTER ELYSE LOM/INT
HOMAR INT/VHP VORTAC 33.95 DME (IAF)	VUDUY INT (NOPT)	325.00 / 1.13 (HDG) & 252.01 / 0.65 (I-MQJ)	2700	CLIMB TO 1400 THEN CLIMBING LEFT TURN TO 2400 ON SHB VOR/DME R-334 TO SHB VOR/DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 154.00 INBOUND. CHART FAS OBST: 969 TREE 395028N/0855305W CHART CIRCLING ICON.
VUDUY INT (IF)	ELYSE LOM/INT	252.01 / 5.57 (I-MQJ)	2700	

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. **HOLD E ELYSE, RT, 252.01 INBOUND, 2700 FT. IN LIEU OF PT (IAF)**
3. FAC: 252.01 FAF: ELYSE LOM/INT DIST FAF TO MAP: 5.41 THLD: 5.41
4. MIN. ALT: **ELYSE LOM/INT 2700**
5. DIST TO THLD FROM OM: 5.41 MM: - IM: - 150 HAT: - 100 HAT: - GS ANT: **1003**
6. MIN GS INCPT: 2700 GS ALT AT: - OM: 2660 MM: - IM: -
7. GS ANGLE: 3.00 TCH: 53.0
8. MSA FROM: **SHB VOR/DME 3100**

MAG VAR: **2W** EPOCH YEAR: **1985**

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X						
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
S-ILS 25	1060	1/2	200	1060	1/2	200	1060	1/2	200	1060	1/2	200			
S-LOC 25	1220	1/2	360	1220	1/2	360	1220	5/8	360	1220	5/8	360			
CIRCLING	1340	1	478	1340	1	478	1360	1 1/2	498	1660	2 1/2	798			

NOTES:
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT HOMAR ON V50 EASTBOUND AND ON V221 SOUTHBOUND.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE INDIANAPOLIS INTL ALTIMETER SETTING AND INCREASE ALL DA 55 FEET AND ALL MDA 60 FEET, INCREASE S-LOC 25 CATS C/D VISIBILITY 1/8 MILE AND CIRCLING CAT D VISIBILITY 1/4 MILE.



CITY AND STATE INDIANAPOLIS, IN	ELEVATION: 862 TDZE: 860 AIRPORT NAME: INDIANAPOLIS RGNL	FACILITY IDENTIFIER: I-MQJ	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 25, AMDT 3 17 AUGUST 2017	SUP: AMDT: 2E DATED 01/05/2017
---	---	--------------------------------------	---	--