

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (RNP) - STANDARD,
INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
KUSAC (FAF)	RW35L (MAP) (FO) (TF)	352.05 / 6.28	
RW35L (MAP)	ZAMLO (TF) (FB) (RNP 1.00)	352.05 / 8.23	
ZAMLO	JEPMA (TF) (FB) (RNP 1.00)	037.00 / 8.0	
JEPMA	ADANE (TF) (FO) (RNP 1.00)	117.55 / 11.27	9000

NOTES, (CONT.):

- CHART PROFILE NOTE: SEE PLANVIEW FOR MULTIPLE IF LOCATIONS.
- CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT DRAKE ON V83 SOUTHEAST BOUND AND V389 SOUTHBOUND.
- CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT FSHER ON V244 EASTBOUND.
- CHART NOTE: FOR INOPERATIVE MALSR INCREASE RNP 0.15 VISIBILITY ALL CATS TO RVR 5000.
- CHART NOTE: RADAR MONITORING REQUIRED WHEN R-2601 IN USE.
- CHART SPEED ICON IN PLANVIEW AT HUNSI: MAX 180 KIAS.



CITY AND STATE COLORADO SPRINGS, CO	ELEVATION: 6187 TDZE: 6075 AIRPORT NAME: CITY OF COLORADO SPRINGS MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (RNP) Z RWY 35L, AMDT 1A 17 AUGUST 2017	SUP:
				AMDT: 1
				DATED: 05/26/2016