FEDERAL AVIATION ADMINISTRATION

FLIGHT STANDARDS SERVICE

ILS STANDARD INSTRUMENT APPROACH PROCEDURE

TITLE 14 CFR PART 97.29

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

AIRPORT JAMES M COX DAYTO	N INTL KDAY	PROCEDURE NAME ILS OR LOC RWY 24L	ORIGINAL/AMENDMENT 11		<u>CITY</u> DAYTON	<u>STATE</u> OH
AIRPORT ELEVATION 1009	TDZE 1007	SUPERSEDED ILS OR LOC RWY 24L	ORIGINAL/AMENDMENT 10A	DATED 05/24/2018	MAG VAR 6W	EPOCH YEAR 2020
FACILITY I-EGK	COORDINATES OF FACILITIES	ACTUAL EFFECTIVE DATE 3 JANUARY 2019	REQUIRED EFFECTIVE DATE ROUTINE	CANCEL	<u>/SUSPEND</u>	

THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 18-26.

FROM	FIX TYPE	<u>T0</u>	FIX TYPE	LEG TYPE	FO/FB	<u>RNP</u>	COURSE	DISTANCE	ALTITUDE
ROD VORTAC		TARRY INT/I-EGK 17.48 DME					162.01	15.20	2800
TARRY INT/I-EGK 17.48 DME	IAF	JAVDO INT/I-EGK 12.18 DME					241.36 (I-EGK)	5.30	2800
JAVDO INT/I-EGK 12.18 DME	IF	ZAMBO INT/I-EGK 6.23 DME					241.36 (I-EGK)	5.95	2600

MISSED APPROACH

MAP:

ILS: DA

LOC: 4.86 NM AFTER ZAMBO INT/I-EGK 6.23 DME

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 3000 ON HEADING 241 AND DQN R-180 TO MIMMS/DQN 18 DME AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS (DO NOT CHART): CLIMB TO 1500 THEN CLIMBING LEFT TURN TO 3000 ON HEADING 045 AND ON ROD VORTAC R-194 TO ZAMBO INT/I-EGK 6.23 DME AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3000.

PROFILE:							
1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF (IAF)			
2. PROFILE STARTS AT JAVDO							
3. FAC: 2	41.36 FAF: ZAMBO DME	INT/I-EGK 6.23 DIST FAF	TO MAP: 4.86	DIST FAF TO THLD: 4.86			
4. MIN ALT	: JAVDO INT/I-EGK 12.	18 DME 2800, ZAMBO INT/I-EGK	6.23 DME 2600				
5. DIST TO	THLD FROM PFAF: 4.86	6 MM: IM:	150 HAT:	GS ANT: 900			
6. MIN GS I	NCPT: 2600	GS ALT AT FAF : ZAMBO INT	T/I-EGK 6.23 DME 2600	OM:	MM:	IM:	
7. GP ANG	LE: 3.00 3	34:1: 20:1:	TCł	H: 50.0			
8. MSA FRO	DM: DQN VOR/DME 310	0					

EQUIPMENT REQUIREMENTS NOTES:

DME REQUIRED.

23

AIRPORT	AIRPORT ID	PROCEDURE NAME	ORIGINAL/AMENDMENT	<u>CITY</u>	<u>STATE</u>
JAMES M COX DAYTON INTL	KDAY	ILS OR LOC RWY 24L	11	DAYTON	ОН

NOTES:

CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED. CHART PROFILE NOTE: VGSI AND ILS GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA.

ADDITIONAL FLIGHT DATA:

HOLD S, LT, 359.99 INBOUND

CHART IN PLANVIEW: ROD VORTAC R-194 AND DQN VOR/DME R-108 AT ZAMBO CHART ARRIVAL HOLDING AT TARRY: HOLD NE, RT, 241.36 INBOUND, 2800. CHART CIRCLING ICON. CHART VDP AT 2.57 DME* DISTANCE VDP TO THLD 1.20 NM * LOC ONLY FAS OBST: 1179 AAO 395554N/0840736W. CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD NE ZAMBO INT/I-EGK 6.23 DME, RT, 241.36 INBOUND.

IBOUND.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

AL	TE	RI	NA'	TE:	NA

ILS: STANDARD; LOC: STANDARD

CATEGORY:		Α			в			С			D			Е	
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	<u>VIS</u>	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
S-ILS 24L**	1207	2400	200	1207	2400	200	1207	2400	200	1207	2400	200			
S-LOC 24L	1440	2400	433	1440	2400	433	1440	4000	433	1440	4000	433			
CIRCLING	1580	1	571	1580	1	571	1580	1 1/2	571	1640	2	631			

CHANGES - REASONS

1. CHANGED ALL REFERENCE OF ZAMBO OM/INT TO ZAMBO INT/EGK 6.23 DME - ADDED DME TO EGK ILS.

2. TERMINAL ROUTES: CHANGED TARRY FROM AN INT TO INT/EGK 17.48 DME - ADDED DME TO EGK ILS AND ALIGNED TO FINAL.

3. TERMINAL ROUTES: ADDED ROUTE FROM TARRY TO JAVDO AND APPLICABLE DATA - ADDED JAVDO PER ATC REQUEST.

4. TERMINAL ROUTES: ADDED ROUTE FROM JAVDO TO ZAMBO AND APPLICABLE DATA - ADDED JAVDO PER ATC REQUEST.

5. LINE 1: DELETED PROCEDURE TURN AND APPLICABLE DATA - ATC REQUEST.

6. LINE 3: CHANGED FAC FROM 241.37 TO 241.36 - NEW ILS DATA.

7. ADDITIONAL FLIGHT DATA: ADDED CHART ARRIVAL HOLDING AT TARRY: HOLD NE, RT, 241.36 INBOUND, 2800 - PER ATC REQUEST.

8. MINIMUMS: CHANGED S-LOC 24L MDA/HAT ALL CATS FROM 1500/493 TO 1440/433; CAT C/D RVR FROM 5000 TO 4000 - NEW FINAL EVALUATION.

9. MISSED APPROACH: CHANGED ALL REFERENCE OF MIMMS INT TO MIMMS/DQN 15.73 DME - RICHMOND VORTAC BEING DECOMMISSIONED.

10. ADDED EQUIPEMENT REQUIREMENTS NOTE: DME REQUIRED - CRITERIA: 8260.19H, PARA 8-6-8 A(2).

11. DELETED INOP NOTE - INCREASE NOW MATCHES INOP TABLE.

12. LINE 3: DIST FAF TO MAP/THLD CHANGED FROM 4.69 TO 4.86 - ZAMBO RELOCATED.

11/7/18: THIS IS A CORRECTED COPY OF THE FORM APPROVED ON 10/17/18:

1. TERMINAL ROUTES: CHANGED ROD VORTAC TO TARRY INT COURSE FROM 157.01 TO 162.01 - TO CORRECT AN ADMINISTRATIVE ERROR.

2. ALTERNATE MISSED APPROACH INSTRUCTIONS: CHANGED ZAMBO DME FROM 4.86 TO 6.23 - TO CORRECT AN ADMINISTRATIVE ERROR.

3. ADDITIONAL FLIGHT DATA: ALTERNATE MA HOLDING, CHANGED ZAMBO DME FROM 4.86 TO 6.23 - TO CORRECT AN ADMINISTRATIVE ERROR.

AIRPORT JAMES M COX DAYTON INTL	AIRPORT ID KDAY	PROCEDURE NAME ILS OR LOC RWY 24L	ORIGINAL/AMENDMENT 11	CITYSTATEDAYTONOH
<u>COORDINATED WITH:</u> A4A 🗌 ALPA 🔀 AOPA 🗙		OTHER: ZID, COLUMBUS APP CON,	DAY ATCT, AMGR, ATA	
FLIGHT CHECKED BY Digitally sig GLEN B FREEMAN DAVID DA OCt 17, 2 DEVELOPED BY JAMES ROGERS Nov 07, 2018	NNER	<u>OFFICE</u> FICO <u>OFFICE</u> AJV-5421	DATE 9/5/18 DATE 04/20/2018	
APPROVED BYDigitally sJULIE MORGANROBERT G	signed by HAMILTON 9, 2018	OFFICE AJV-5420	DATE	<u>TITLE</u> MANAGER