

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (RNP) - STANDARD,
INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
VECKI (IF)	EGIPT (TF) (FB) (RNP 1.00)	173.83 / 6.01	1500
EGIPT (FAF)	RW17 (MAP) (TF) (FO) (RNP 0.30)	173.82 / 4.39	
RW17 (MAP)	WOPNA (TF) (FB) (RNP 1.00)	173.82 / 5.59	
WOPNA	NANLE (RF) (FB) (RNP 1.00)	(5.30 NM RADIUS CW (UKJOJ)) / 17.02	
NANLE	ANDES (TF) (FO) (RNP 1.00)	357.79 / 8.86	5000

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON UPP VORTAC AIRWAY RADIALS 200 CW 287.
 CHART NOTE: FOR INOPERATIVE ALS, INCREASE RNP 0.30 ALL CATS VISIBILITY TO 1 1/2 MILE.



CITY AND STATE KAILUA/KONA, HI	ELEVATION: 47 TDZE: 47 AIRPORT NAME: ELLISON ONIZUKA KONA INTL AT KEAHOLE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (RNP) Z RWY 17, ORIG-B 24 MAY 2018	SUP:
				AMDT: ORIG-A
				DATED: 11/13/2014