

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.			
TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW17 CLIMB TO 7000 DIRECT XANZI AND HOLD, CONTINUE CLIMB-IN-HOLD TO 7000. ADDITIONAL FLIGHT DATA: HOLD S, RT, 354.69 INBOUND. CHART FAS OBST: 2544 TREE 352705N/1001236W CHART CIRCLING ICON. VUGKU TO RW17: 3.00/40. CHART HEMPHILL COUNTY AWOS.			
BRISC	FIVWI (TF) (FB) (RNP 2.00)	045.66 / 10.71	7000				
OKWUS (IAF)	LUDYI (TF) (FB) (RNP 1.00)	264.78 / 8.00	7000				
FIVWI (IAF)	LUDYI (TF) (FB) (RNP 1.00)	084.59 / 7.50	7000				
EYMUW (IAF)	LUDYI (TF) (FB) (RNP 1.00)	174.78 / 15.91	7000				
LUDYI (IF)	VUGKU (TF) (FB) (RNP 1.00)	174.68 / 9.00	4300				
(SEE FORM 8260-10)							

1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)							
2. PROFILE STARTS AT LUDYI							
3. FAC: 174.68 FAF: VUGKU DIST FAF TO MAP: 5.74 THLD: _____							
4. MIN. ALT: LUDYI 7000, VUGKU 4300, YIBUL/2.50 NM TO RW17 3260							
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____							
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____							
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR							
8. MSA FROM: RW17 4600				MAG VAR: 5E		EPOCH YEAR: 2020	

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		X			
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
CIRCLING	2980	1	510	3000	1	530	3020	1 1/2	550		NA				

NOTES:

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: USE HEMPHILL COUNTY ALTIMETER SETTING.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT BRISC ON V272-440 WESTBOUND.

CITY AND STATE	ELEVATION: 2470 TDZE:	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
WHEELER, TX	AIRPORT NAME:	RNAV	RNAV (GPS)-A, AMDT 1	AMDT: ORIG
	WHEELER MUNI		17 AUGUST 2017	DATED 04/27/2017

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
VUGKU (FAF)	YIBUL/2.50 NM TO RW17 (TF) (FB) (RNP 0.30)	174.68 / 3.24	
YIBUL/2.50 NM TO RW17	RW17 (MAP) (TF) (FO) (RNP 0.30)	174.68 / 2.50	
RW17 (MAP)	2870 MSL (CA)	174.68	
2870 MSL	XANZI (DF) (FO) (RNP 1.00)		7000

QUALITY
5
CHECKED

CITY AND STATE
WHEELER, TX

ELEVATION: 2470 TDZE:
AIRPORT NAME:
WHEELER MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS)-A, AMDT 1
17 AUGUST 2017

SUP:
AMDT: ORIG
DATED: 04/27/2017