

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW35						
BRISC		WUXOR (TF) (FB) (RNP 2.00)		159.64 / 23.58				7000		CLIMB TO 7000 DIRECT LUDY AND HOLD, CONTINUE CLIMB-IN-HOLD TO 7000.						
WUDPI		WUXOR (TF) (FB) (RNP 2.00)		099.27 / 8.22				7000								
ZASPA (IAF)		XANZI (TF) (FB) (RNP 1.00)		264.78 / 8.00				7000								
WUXOR (IAF)		XANZI (TF) (FB) (RNP 1.00)		084.50 / 9.80				7000								
XANZI (IF)		IYTEY (TF) (FB) (RNP 1.00)		354.69 / 9.50				4000								
(SEE FORM 8260-10)										ADDITIONAL FLIGHT DATA: HOLD N, RT, 174.68 INBOUND. CHART FAS OBST: 2624 TREE 352501N/1001233W CHART CIRCLING ICON. IYTEY TO RW35: 3.00/40. CHART HEMPHILL COUNTY AWOS.						
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																
2. PROFILE STARTS AT XANZI																
3. FAC: 354.69 FAF: IYTEY _____ DIST FAF TO MAP: 4.68 THLD: _____																
4. MIN. ALT: XANZI 7000, IYTEY 4000, JOKDI/2.51 NM TO RW35 3300																
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR																
8. MSA FROM: RW35 4600																
MAG VAR: 5E EPOCH YEAR: 2020																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		X						
CATEGORY ==>		A			B			C			D			E		
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
CIRCLING		2980	1	510	3000	1	530	3020	1 1/2	550		NA				
NOTES: CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: USE HEMPHILL COUNTY ALTIMETER SETTING.																
(CONTINUED ON PAGE 2)																
CITY AND STATE WHEELER, TX		ELEVATION: 2470 TDZE: AIRPORT NAME: WHEELER MUNI			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-B, AMDT 1 17 AUGUST 2017					SUP: AMDT: ORIG DATED 04/27/2017				

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
IYTEY (FAF)	JOKDI/2.51 NM TO RW35 (TF) (FB) (RNP 0.30)	354.69 / 2.17	
JOKDI/2.51 NM TO RW35	RW35 (MAP) (TF) (FO) (RNP 0.30)	354.69 / 2.51	
RW35 (MAP)	2870 MSL (CA)	354.69	
2870 MSL	LUDYI (DF) (FO) (RNP 1.00)		7000

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT BRISC ON V272-440 WESTBOUND AND V402-440 EASTBOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT WUDPI ON V140 WESTBOUND.

QUALITY
5
CHECKED

CITY AND STATE

WHEELER, TX

ELEVATION: 2470
AIRPORT NAME:

WHEELER MUNI

TDZE:

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS)-B, AMDT 1

17 AUGUST 2017

SUP:

AMDT: ORIG

DATED: 04/27/2017