

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.														
TERMINAL ROUTES											MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW27 CLIMB TO 3100 DIRECT ANWAF AND HOLD. ADDITIONAL FLIGHT DATA: HOLD W, RT, 092.08 INBOUND. CHART FAS OBST: 545 TOWER 322630N/0862709W. DISTANCE TO THLD FROM 283 HAT: 0.79 NM. CHART VDP AT 1.80 NM TO RW27* *LNAV ONLY. WAAS CHANNEL # 62941 REFERENCE PATH ID: W27A CHART CIRCLING ICON. LTP HAE: 32.2 M									
ZOREL (IF/IAF)		JEMER (TF) (FB) (RNP 1.00)			272.38 / 9.54				2300											
JEMER (FAF)		RW27 (MAP) (TF) (FO) (RNP 0.30)			272.28 / 6.46															
RW27 (MAP)		496 MSL (CA)			272.28				3100											
496 MSL		ANWAF (DF) (FO) (RNP 1.00)																		
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD E ZOREL, RT, 272.38 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 272.28 FAF: JEMER DIST FAF TO MAP: 6.46 THLD: 6.46 4. MIN. ALT: ZOREL 3000, JEMER 2300 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2300 GS ALT AT: JEMER 2300 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 45.0 34:1 IS NOT CLEAR 8. MSA FROM: _____																	MAG VAR: 3W		EPOCH YEAR: 2015	
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @								
CATEGORY =====>		A			B			C			D			E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA					
LPV DA	496	7/8	283	496	7/8	283	496	7/8	283	496	7/8	283								
LNAV/VNAV DA	659	1 3/8	446	659	1 3/8	446	659	1 3/8	446	659	1 3/8	446								
LNAV MDA	820	1	607	820	1	607	820	1 3/4	607	820	1 3/4	607								
CIRCLING	1000	1	775	1000	1	775	1080	2 1/2	855	1140	3	915								
NOTES: CHART NOTE: CIRCLING TO RWY 9 NA AT NIGHT. @ CAT C 900-2 1/2, CAT D 1000-3 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). CHART NOTE: RWY 27 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA.																				
CITY AND STATE		ELEVATION: 225 TDZE: 213			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:					SUP:								
PRATTVILLE, AL		AIRPORT NAME:					RNAV (GPS) RWY 27, AMDT 1					AMDT: ORIG-D								
		PRATTVILLE - GROUBY FIELD					24 MAY 2018					DATED 04/02/2015								

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	182/30 CW 002/30 (NOPT) 182/20 CW 002/20	182/20 CW 002/20 ZOREL (IF/IAF) (FB)	3500 3000
2.	002/30 CW 182/30 002/20 CW 182/20	002/20 CW 182/20 ZOREL (IF/IAF) (FO)	3500 3000

QUALITY
10

CHECKED

CITY AND STATE

PRATTVILLE, AL

ELEVATION: 225

TDZE: 213

AIRPORT NAME:

PRATTVILLE - GROUBY FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 27, AMDT 1

24 MAY 2018

SUP:

AMDT: ORIG-D

DATED: 04/02/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	1A9
RUNWAY	RW27
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W27A
LTP/FTP LATITUDE	322619.8020N
LTP/FTP LONGITUDE	0863014.1605W
LTP/FTP ELLIPSOIDAL HEIGHT	+00322
FPAP LATITUDE	322618.5605N
FPAP LONGITUDE	0863159.4320W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1104
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 D1200EAC

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00604
FPAP ORTHOMETRIC HEIGHT	+00604

CITY AND STATE

PRATTVILLE, AL

ELEVATION: 225

TDZE: 213

AIRPORT NAME:

PRATTVILLE - GROUBY FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 27, AMDT 1

24 MAY 2018

SUP:

AMDT:

DATED:

 QUALITY
10

CHECKED

ORIG-D

04/02/2015