

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	
STOOP	YANBU (TF) (FB) (RNP 2.00)	162.13 / 36.88	2500	LNAV: RW28 (DO NOT EXCEED 210 KIAS UNTIL TURN COMPLETION) CLIMBING LEFT TURN TO 2000 DIRECT UGLEE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 010.00 INBOUND. FAS OBST: 208 SHIP 263500N/0800124W RUCOG TO RW28: 4.00/45. CHART CIRCLING ICON. FAC CROSSES RWY 28 THLD.
YANBU (IAF)	CUVMO (NOPT) (TF) (FB) (RNP 1.00)	209.02 / 7.00	2500	
MRLIN (IAF)	CUVMO (NOPT) (TF) (FB) (RNP 1.00)	313.71 / 8.42	2500	
CUVMO (IF/IAF)	RUCOG (TF) (FB) (RNP 1.00)	279.04 / 6.29	1700	
RUCOG (FAF)	RW28 (MAP) (TF) (FO) (RNP 0.30)	278.99 / 3.87		
(SEE FORM 8260-10)				

- PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
- HOLD E CUVMO, LT, 279.04 INBOUND, 2500 FT. IN LIEU OF PT (IAF)
- FAC: 278.99 FAF: RUCOG DIST FAF TO MAP: 3.87 THLD: 3.87
- MIN. ALT: CUVMO 2500, RUCOG 1700
- DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____
- MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____
- GS ANGLE: _____ TCH: _____
- MSA FROM: RW28 2600

MAG VAR: **7W** EPOCH YEAR: **2020**

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
CIRCLING	460	1	446	520	1	506	580	1 1/2	566		NA				

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT STOOP ON V295 NORTHWEST BOUND AND ON V492-537 NORTH BOUND.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT MRLIN ON BR68V NORTHEAST BOUND, ON BR64V-68V EAST
 (CONTINUED ON PAGE 2)



CITY AND STATE WEST PALM BEACH, FL	ELEVATION: 14 TDZE: AIRPORT NAME: PALM BEACH COUNTY PARK	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-B, AMDT 1 1 FEBRUARY 2018	SUP: AMDT: ORIG DATED 08/22/2013
--	--	-------------------------------------	---	--

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
RW28 (MAP)	414 MSL (CA)	278.99	
414 MSL	UGLEE (DF) (FO) (RNP 1.00)		2000

NOTES, (CONT.):

BOUND AND ON BR54V-55V SOUTHEAST BOUND.
 CHART NOTE: RWY 28 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
 CHART NOTE: CIRCLING TO RWYS 4, 16, 22, 28, 34 NA AT NIGHT.



CITY AND STATE WEST PALM BEACH, FL	ELEVATION: 14 AIRPORT NAME: PALM BEACH COUNTY PARK	TDZE:	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-B, AMDT 1 1 FEBRUARY 2018	SUP:
					AMDT: ORIG
					DATED: 08/22/2013