

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
LDA STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
CROOZ/I-ASO 17.00 DME/RADAR (IF)	MAUDY INT/I-ASO 10.00 DME	149.00 / 7.00 (I-ASO)	3000
MAUDY INT/I-ASO 10.00 DME	MINIE INT/I-ASO 6.34 DME	149.00 / 3.66 (I-ASO)	2000

MAP: LDA: 2.84 NM AFTER MINIE INT/I-ASO 6.34 DME OR AT JEVGA INT/I-ASO 3.50 DME FIX

CLIMB TO 1800 DIRECT DCA VOR/DME AND ON DCA VOR/DME R-185 TO OXONN NDB/DCA 5.62 DME AND HOLD.

ALTERNATE MA (DO NOT CHART): CLIMB TO 1700 THEN CLIMBING RIGHT TURN TO 1800 DIRECT OXONN NDB AND HOLD (ADF REQUIRED).

ADDITIONAL FLIGHT DATA:
 HOLD S, LT, 004.67 INBOUND.
 FAS OBST: 558 AAO 385724N/0770727W.
 CHART CIRCLING ICON.
 CHART P-56A/B.
 CHART P-73.
 FAC CROSSES RWY C/L EXTENDED 56 FT FROM THLD.
 CHART PLANVIEW NOTE: RADAR REQUIRED.
 CHART PLANVIEW NOTE: LOC OFFSET 37.50 DEGREES.

- PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
- PROFILE STARTS AT CROOZ
- FAC 149.00 FAF MINIE INT/I-ASO 6.34 DME DIST FAF TO MAP 2.84 THLD _____
- MIN. ALT CROOZ 3000, MAUDY 3000, MINIE 2000
- MSA FROM: DCA VOR/DME 2600

MAG VAR: 11W EPOCH YEAR: 2020

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A			LDA: @					
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-LDA 19	1100	3	1087	1100	3	1087	1100	3	1087	1100	3	1087			
CIRCLING	1100	3	1086	1100	3	1086	1100	3	1086	1100	3	1086			

NOTES:

CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY.
 CHART NOTE: CIRCLING NA NORTHEAST OF RWY 15-33.
 CHART NOTE: ADF OR DME REQUIRED.
 CHART PLANVIEW AND PROFILE NOTE: FLY VISUAL TO AIRPORT 149.00 DEGREES 3.37 NM.
 (CONTINUED ON PAGE 2)

@ CAT A, B, C, D 1100-3



CITY AND STATE WASHINGTON, DC	ELEVATION: 14 TDZE: 13	FACILITY IDENTIFIER: I-ASO	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: LDA Y RWY 19, AMDT 1A 29 MARCH 2018	SUP
	AIRPORT NAME: RONALD REAGAN WASHINGTON NATIONAL			AMDT 1
	DATE 10/12/2017			

**LDA STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.25**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROHIBITED AREA (P-56) 1.5 NM NORTH OF DCA - AVOID SURFACE TO 18000 MSL.



CITY AND STATE WASHINGTON, DC	ELEVATION: 14 AIRPORT NAME: RONALD REAGAN WASHINGTON NATIONAL	TDZE: 13	FACILITY IDENTIFIER: I-ASO	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: LDA Y RWY 19, AMDT 1A 29 MARCH 2018	SUP:
					AMDT: 1
					DATED: 10/12/2017