



**US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (RNP) - STANDARD,**  
**INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES, (CONT.):**

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
FIVUD	HESLO (TF) (FB) (RNP 0.65)	326.63 / 1.30	
HESLO	GTN NDB (TF) (FO) (RNP 0.80)	326.61 / 3.26	2200

**NOTES, (CONT.):**

CHART PLANVIEW NOTE: PROHIBITED AREA (P-56) 1.5 NM NORTH OF DCA - AVOID SURFACE TO 18,000 MSL.  
 CHART NOTE: FOR INOPERATIVE ALS, INCREASE RNP 0.30 ALL CATS VISIBILITY TO 1 3/4 MILE.



CITY AND STATE <b>WASHINGTON, DC</b>	ELEVATION: 14 AIRPORT NAME: <b>RONALD REAGAN WASHINGTON NATIONAL</b>	TDZE: 14	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (RNP) RWY 1, AMDT 1B</b> 26 APRIL 2018	SUP:
					AMDT: <b>1A</b>
					DATED: <b>05/29/2014</b>