

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW35 CLIMB TO 4600 DIRECT DUKRE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 170.29 INBOUND. CHART FAS OBST: 2172 POLE 371311N/0991910W. DISTANCE TO THLD FROM 361 HAT: 1.03 NM. WAAS CHANNEL # 86839 REFERENCE PATH ID: W35A CHART CIRCLING ICON. *LNAV ONLY. LTP HAE: 604.6 M						
IDICU (IAF)		GECKS (NOPT) (TF) (FB) (RNP 1.00)			050.24 / 7.00			4600								
JANAX (IAF)		GECKS (NOPT) (TF) (FB) (RNP 1.00)			290.39 / 7.00			4600								
GECKS (IF/IAF)		BOGVE (TF) (FB) (RNP 1.00)			350.31 / 7.84			3600								
BOGVE (FAF)		HAGMI/2.40 NM TO RW35 (TF) (FB) (RNP 0.30)			350.30 / 2.27											
HAGMI/2.40 NM TO RW35		RW35 (MAP) (TF) (FO) (RNP 0.30)			350.30 / 2.40											
(SEE FORM 8260-10)																
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S GECKS, LT, 350.31 INBOUND, 4600 FT. IN LIEU OF PT (IAF) 3. FAC: 350.30 FAF: BOGVE DIST FAF TO MAP: 4.67 THLD: 4.67 4. MIN. ALT: GECKS 4600, BOGVE 3600, HAGMI/2.40 NM TO RW35 2860* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 3600 GS ALT AT: BOGVE 3600 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR 8. MSA FROM: _____																
										MAG VAR: 5E			EPOCH YEAR: 2020			
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @						
CATEGORY ==>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	2443	1 1/4	361	2443	1 1/4	361	2443	1 1/4	361		NA					
LNAV/VNAV DA	2461	1 1/4	379	2461	1 1/4	379	2461	1 1/4	379		NA					
LNAV MDA	2540	1	458	2540	1	458	2540	1 3/8	458		NA					
CIRCLING	2620	1	534	2620	1	534	2940	2 1/2	854		NA					
NOTES: CHART NOTE: BARO-VNAV NA WHEN USING PRATT ALTIMETER SETTING. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: RWY 35 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.																
@ NA WHEN LOCAL WEATHER NOT AVAILABLE. @ CAT C 900-2 1/2																
QUALITY 25 CHECKED																
(CONTINUED ON PAGE 2)																
CITY AND STATE		ELEVATION: 2086 TDZE: 2082			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
COLDWATER, KS		AIRPORT NAME:			COMANCHE COUNTY		RNAV (GPS) RWY 35, ORIG-A				AMDT: ORIG					
							24 MAY 2018				DATED 08/18/2016					

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW35 (MAP)	2443 MSL (CA)	350.30	
2443 MSL	DUKRE (DF) (FO) (RNP 1.00)		4600

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PRATT ALTIMETER SETTING AND INCREASE LPV DA TO 2554 AND LNAV/VNAV DA TO 2572 AND ALL MDA 120 FEET; INCREASE LPV ALL CATS VISIBILITY 1/8 SM, LNAV/VNAV ALL CATS VISIBILITY 1/8 SM, LNAV CAT C VISIBILITY 1/4 SM, AND INCREASE CIRCLING CAT C VISIBILITY 1/2 SM.

TAA

	FROM	TO	ALT
1.	290/30 CW 050/30 (NOPT)	GECKS (IF/IAF) (FB)	4600
2.	050/30 CW 170/30	IDICU (IAF) (FB)	4600
3.	170/30 CW 290/30	JANAX (IAF) (FB)	4600

QUALITY
25
CHECKED

CITY AND STATE

COLDWATER, KS

ELEVATION: 2086

TDZE: 2082

AIRPORT NAME:

COMANCHE COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, ORIG-A

24 MAY 2018

SUP:

AMDT:

ORIG

DATED:

08/18/2016

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	3K8
RUNWAY	RW35
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W35A
LTP/FTP LATITUDE	371300.1185N
LTP/FTP LONGITUDE	0991953.0455W
LTP/FTP ELLIPSOIDAL HEIGHT	+06046
FPAP LATITUDE	371429.0290N
FPAP LONGITUDE	0992002.1890W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1376
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 D04BC658

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+06322
FPAP ORTHOMETRIC HEIGHT	+06322

QUALITY
25
CHECKED

CITY AND STATE COLDWATER, KS	ELEVATION: 2086 AIRPORT NAME: COMANCHE COUNTY	TDZE: 2082 	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG-A 24 MAY 2018	SUP:
					AMDT: ORIG
					DATED: 08/18/2016