

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

**RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.


TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
ADLIW (IAF)	CIKEB (NOPT) (FB)	076.35 / 5.00	2600	LNAV: RW35
FISAS (IAF)	CIKEB (NOPT) (FB)	256.45 / 5.00	2600	
CIKEB (IF/IAF)	JIVEP (FB)	346.40 / 6.10	2100	CLIMBING RIGHT TURN TO 2600 DIRECT CIKEB AND HOLD.
JIVEP (FAF)	RW35 (MAP) (FO)	346.39 / 4.21		
RW35 (MAP)	1102 MSL	346.39		
1102 MSL	CIKEB (FO)		2600	<b>ADDITIONAL FLIGHT DATA:</b> FAS OBST: 849 AAO 290438N/0985512W FAS OBST: 909 AAO 290410N/0985451W CHART: CASTROVILLE AWOS. CHART: TDZE 702. CHART: APT ELEV 702.

- PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
- HOLD S CIKEB, RT, 346.40 INBOUND, 2600 FT. IN LIEU OF PT (IAF)
- FAC: 346.39 FAF: JIVEP DIST FAF TO MAP: 4.21 THLD: 4.21
- MIN. ALT: CIKEB 2600, JIVEP 2100
- DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
- MIN GS INCPT:        GS ALT AT:        OM:        MM:        IM:
- GS ANGLE:        TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 7E EPOCH YEAR: 1990

MINIMUMS															
TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A X								
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1140	1	438	1140	1	438		NA			NA				
CIRCLING	1380	1	678	1380	1	678		NA			NA				

NOTES:  
 CHART NOTE: DME/DME RNP-0.3 NA.  
 CHART NOTE: USE CASTROVILLE MUNI ALTIMETER SETTING; WHEN NOT RECEIVED, USE HONDO MUNI ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET.  
 CHART NOTE: NIGHT LANDING: RWY 35 NA.  
 (SEE FORM 8260-10)



CITY AND STATE DEVINE, TX	ELEVATION: 702 TDZE: 702 AIRPORT NAME: DEVINE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG-A 29 MAY 2014	SUP: AMDT: ORIG DATED 07/02/2009
------------------------------	----------------------------------------------------------	------------------------------	------------------------------------------------------------------------------------	----------------------------------------

**US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**


Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES, (CONT.):**

**CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.  
CHART PROFILE NOTE: DESCENT ANGLE NA.**

**TAA**

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	256/30 CW 076/30 (NOPT)	CIKEB (IF/IAF) (FB)	2600
2.	076/30 CW 166/30	ADLIW (IAF) (FB)	2600
3.	166/30 CW 256/30	FISAS (IAF) (FB)	2700



CITY AND STATE

DEVINE, TX

ELEVATION: 702

TDZE: 702

AIRPORT NAME:

DEVINE MUNI

FACILITY IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, ORIG-A

29 MAY 2014

SUP:

AMDT:

ORIG

DATED:

07/02/2009



**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICES - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	ADLIW	ADLIW	010	IAF	IF		FB					
	ADLIW	CIKEB	020		TF		FB	1.0	076.4 (083.4T)	005.0	AA 02600	
	CIKEB	CIKEB	010	IAF	HF	R	FO		346.4 (353.4T)	004.0	AA 02600	
	FISAS	FISAS	010	IAF	IF		FB					
	FISAS	CIKEB	020		TF		FB	1.0	256.5 (263.5T)	005.0	AA 02600	
		CIKEB	010	FACF	IF		FB				AA 02600	
		JIVEP	020	FAF	TF		FB	0.5	346.4 (353.4T)	006.1	AA 02100	
		RW35	030	MAP	TF		FO	0.3	346.4 (353.4T)	004.2	AT 01140	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		346.4 (353.4T)		AA 01102	
	CIKEB	050		DF	R	FO				AA 02600	
	CIKEB	060		HM	R	FO		346.4 (353.4T)	004.0	AA 02600	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	ADLIW	N285710.74	W0990047.12	N2857.179	W09900.785
	CIKEB	N285745.43	W0985507.42	N2857.757	W09855.124
	FISAS	N285819.88	W0984927.66	N2858.331	W09849.461
	JIVEP	N290349.73	W0985555.39	N2903.829	W09855.923
	RW35	N290801.50	W0985628.60	N2908.025	W09856.477

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW35	00702	40



CITY AND STATE <b>DEVINE, TX</b>	ELEVATION: <b>702</b>	TDZE: <b>702</b>	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:	<b>DEVINE MUNI</b>	<b>RNAV</b>	<b>RNAV (GPS) RWY 35, ORIG-A</b>	AMDT: <b>ORIG</b>
				29 MAY 2014	DATED: <b>07/02/2009</b>