

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE			ALTITUDE		LNAV: RW06						
ZESLO (IF/IAF)		JOGAM (FB)		063.53 / 6.36			2000		CLIMB TO 3000 DIRECT CIKOB AND HOLD.						
JOGAM (FAF)		UDLEQ/2.60 NM TO RW06 (FB)		063.59 / 3.04											
UDLEQ/2.60 NM TO RW06		RW06 (MAP) (FO)		063.59 / 2.60											
RW06 (MAP)		550 MSL		063.59											
550 MSL		CIKOB (FO)					3000		ADDITIONAL FLIGHT DATA: HOLD NE, RT, 243.76 INBOUND. CHART FAS OBST: 309 SILOS 330439N/0881433W OBST: 459 AAO 330400N/0881822W CHART MERIDIAN 1 EAST MOA. CHART MERIDIAN 1 WEST MOA. CHART CIRCLING ICON.						
1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)										MAG VAR: 2W EPOCH YEAR: 2015					
2. HOLD SW ZESLO, RT, 063.53 INBOUND, 3000 FT. IN LIEU OF PT (IAF)															
3. FAC: 063.59 FAF: JOGAM DIST FAF TO MAP: 5.64 THLD: 5.64															
4. MIN. ALT: ZESLO 3000, JOGAM 2000, UDLEQ/2.60 NM TO RW06 1020															
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:															
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:															
7. GS ANGLE: TCH: 34:1 IS NOT CLEAR															
8. MSA FROM:															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X											
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	640	1	497	640	1	497	640	1 3/8	497	640	1 3/8	497			
CIRCLING	720	1	570	720	1	570	820	1 3/4	670	900	2 1/2	750			
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: USE TUSCALOOSA RGNL ALTIMETER SETTING; WHEN NOT RECEIVED, USE COLUMBUS/W POINT/STARKVILLE ALTIMETER SETTING AND INCREASE ALL MDA 20 FEET, AND CIRCLING CAT C VISIBILITY 1/4 MILE. (SEE FORM 8260-10)															
CITY AND STATE ALICEVILLE, AL		ELEVATION: 150 TDZE: 143 AIRPORT NAME: GEORGE DOWNER		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 6, ORIG-B 26 JUNE 2014				SUP: AMDT: ORIG-A DATED 05/29/2014					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: PROCEDURE NA AT NIGHT.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART PROFILE NOTE: DESCENT ANGLE NA.

TAA

	FROM	TO	ALT
1.	334/30 CW 154/30 (NOPT)	ZESLO (IF/IAF) (FB)	3000
2.	154/30 CW 334/30	ZESLO (IF/IAF) (FO)	3000



CITY AND STATE

ALICEVILLE, AL

ELEVATION: 150

TDZE: 143

AIRPORT NAME:

GEORGE DOWNER

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 6, ORIG-B

26 JUNE 2014

SUP:

AMDT: ORIG-A

DATED: 05/29/2014

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION <u>RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE</u> FLIGHT STANDARDS SERVICES - FAR PART 97.33	Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.
--	---

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION <u>RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE</u> FLIGHT STANDARDS SERVICES - FAR PART 97.33	Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.
--	---



CITY AND STATE ALICEVILLE, AL	ELEVATION: 150 TDZE: 143	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: GEORGE DOWNER		RNAV (GPS) RWY 6, ORIG-B	AMDT: ORIG-A
			26 JUNE 2014	DATED: 05/29/2014

FAA FORM 8260 - 10 / April 2006 (Computer Generated) Page 3 of 4 Pages

FAA FORM 8260 - 10 / April 2006 (Computer Generated) Page 3 of 4 Pages



U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICES - FAR PART 97.33								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
ARINC SUMMARY - 424-18 - RNAV (GPS)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ZESLO	ZESLO	010	IAF	HF	R	FO		063.5 (061.5T)	004.0	AA 03000	
		ZESLO	010	FACF	IF		FB				AA 03000	
		JOGAM	020	FAF	TF		FB	0.5	063.5 (061.5T)	006.4	AA 02000	
		UDLEQ	021	SDF	TF		FB	0.3	063.6 (061.6T)	003.0	AA 01020	
		RW06	030	MAP	TF		FO	0.3	063.6 (061.6T)	002.6	AT 00640	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		063.6 (061.6T)		AA 00550	
		CIKOB	050		DF		FO				AA 03000	
		CIKOB	060		HM	R	FO		243.8 (241.8T)	004.0	AA 03000	
POINT DATA		WAYPOINT		LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS		
		CIKOB		N331217.95		W0875848.78		N3312.299		W08758.813		
		JOGAM		N330331.23		W0881810.24		N3303.521		W08818.171		
		UDLEQ		N330458.26		W0881459.08		N3304.971		W08814.985		
		ZESLO		N330029.23		W0882449.13		N3300.487		W08824.819		
		RW06		N330612.53		W0881215.70		N3306.209		W08812.262		
RUNWAY DATA		RWY	THRESHOLD ELEVATION		TCH							
		RW06	00143		00							



CITY AND STATE ALICEVILLE, AL	ELEVATION: 150 AIRPORT NAME: GEORGE DOWNER	TDZE: 143	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 6, ORIG-B 26 JUNE 2014	SUP: AMDT: ORIG-A DATED: 05/29/2014