

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LP: RW35 LNAV: RW35 CLIMB TO 3200 DIRECT UTOTE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 170.87 INBOUND. CHART FAS OBST: 899 TREE 342754N/0824205W CHART FAS OBST: 899 TREE 342754N/0824205W CHART 1131 TOWER 342627N/0824159W. WAAS CHANNEL # 93734 REFERENCE PATH ID: W35A CHART CIRCLING ICON LTP HAE: 194.1 M MAG VAR: 5W EPOCH YEAR: 2005						
YALBU (IAF)		ZAROM (NOPT) (FB)		080.87 / 6.00				2500								
WUPOX (IAF)		ZAROM (NOPT) (FB)		261.01 / 6.00				2500								
ZAROM (IF/IAF)		HUVSA (FB)		350.94 / 6.90				2500								
HUVSA (FAF)		YUTUC/2.10 NM TO RW35 (FB)		350.92 / 3.30												
YUTUC/2.10 NM TO RW35		RW35 (MAP) (FO)		350.92 / 2.10												
RW35 (MAP)		1160 MSL		350.92												
1160 MSL		UTOTE (FO)						3200								
1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF) 2. HOLD S ZAROM, RT, 350.94 INBOUND, 2500 FT. IN LIEU OF PT (IAF) 3. FAC: 350.92 FAF: HUVSA DIST FAF TO MAP: 5.40 THLD: 5.40 4. MIN. ALT: ZAROM 2500, HUVSA 2500, YUTUC/2.10 NM TO RW35 1440 5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT: 6. MIN GS INCPT: GS ALT AT: OM: MM: IM: 7. GS ANGLE: TCH: 34:1 IS NOT CLEAR 8. MSA FROM:																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @						
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LP MDA	1160	1	423	1160	1	423	1160	1 1/4	423	1160	1 1/4	423				
LNAV MDA	1180	1	443	1180	1	443	1180	1 3/8	443	1180	1 3/8	443				
CIRCLING	1260	1	478	1320	1	538	1440	1 3/4	658	1500	2 1/4	718				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CLEMSON ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET AND INCREASE LP AND CIRCLING CATS C AND D VISIBILITY 1/4 MILE. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. SEE 8260-10																
CITY AND STATE ANDERSON, SC		ELEVATION: 782 THRE: 737 AIRPORT NAME: ANDERSON RGNL		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, AMDT 1 14 NOVEMBER 2013						SUP:				
												AMDT: ORIG				
												DATED 03/15/2007				

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES (CONT'D):

CHART NOTE: RWY 35 STRAIGHT-IN AND CIRCLING AND CIRCLING TO RWY 17/23 NA AT NIGHT.

CHART PROFILE NOTE: DESCENT ANGLE NA.

TAA

	FROM	TO	ALT
1.	261/30 CW 081/30 (NOPT)	ZAROM (IF/IAF) (FB)	2500
2.	081/30 CW 171/30	YALBU (IAF) (FB)	3100
3.	171/30 CW 261/30	WUPOX (IAF) (FB)	3000



CITY AND STATE ANDERSON, SC	ELEVATION: 782 THRE: 737 AIRPORT NAME: ANDERSON RGNL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, AMDT 1 14 NOVEMBER 2013	SUP:
				AMDT: ORIG
				DATED: 03/15/2007

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KAND
RUNWAY	RW35
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W35A
LTP/FTP LATITUDE	342917.6610N
LTP/FTP LONGITUDE	0824229.1730W
LTP/FTP ELLIPSOIDAL HEIGHT	+01941
FPAP LATITUDE	343044.2200N
FPAP LONGITUDE	0824255.4400W
THRESHOLD CROSSING HEIGHT (TCH)	00000.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	00.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

CRC REMAINDER

05FCF2BA

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+02245
FPAP ORTHOMETRIC HEIGHT	+02245

CITY AND STATE

ANDERSON, SC

ELEVATION: 782

THRE: 737

AIRPORT NAME:

ANDERSON RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, AMDT 1

14 NOVEMBER 2013

SUP:

AMDT: ORIG

DATED: 03/15/2007

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KANDK7FR35	AWUPOX	010WUPOXK7EA0E	A	IF						18000		A	JS
SUSAP KANDK7FR35	AWUPOX	020ZAROMK7EA0EE	B	010TF			26100060	+	02500			A	JS
SUSAP KANDK7FR35	AYALBU	010YALBUK7EA0E	A	IF						18000		A	JS
SUSAP KANDK7FR35	AYALBU	020ZAROMK7EA0EE	B	010TF			08090060	+	02500			A	JS
SUSAP KANDK7FR35	AZAROM	010ZAROMK7EA0EE	AR	HF			35090040	+	02500	18000		A	JS
SUSAP KANDK7FR35	R	010ZAROMK7EA0E	I	IF				+	02500	18000		A	JS
SUSAP KANDK7FR35	R	020HUVSAK7EA1E	F	051TF			35090069	+	02500			A	JS
SUSAP KANDK7FR35	R	020HUVSAK7EA2WALP			N	ALNAV						JS	
SUSAP KANDK7FR35	R	021YUTUCK7EA0E	S	031TF			35090033	+	01440			A	JS
SUSAP KANDK7FR35	R	030RW35 K7PG0GY	M	031TF			35090021		01180	000		A	JS
SUSAP KANDK7FR35	R	040	0	M	CA		3509	+	01160			A	JS
SUSAP KANDK7FR35	R	050UTOTEK7EA0EY		DF				+	03200			A	JS
SUSAP KANDK7FR35	R	060UTOTEK7EA0EE	R	HM			17090040	+	03200			A	JS

[illegible][illegible]

CITY AND STATE ANDERSON, SC	ELEVATION: 782 THRE: 737	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 35, AMDT 1 14 NOVEMBER 2013	SUP:
	AIRPORT NAME: ANDERSON RGNL			AMDT: ORIG
				DATED: 03/15/2007

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	WUPOX	WUPOX	010	IAF	IF		FB					
	WUPOX	ZAROM	020		TF		FB	1.0	261.0 (256.0T)	006.0	AA 02500	
	YALBU	YALBU	010	IAF	IF		FB					
	YALBU	ZAROM	020		TF		FB	1.0	080.9 (075.9T)	006.0	AA 02500	
	ZAROM	ZAROM	010	IAF	HF	R	FO		350.9 (345.9T)	004.0	AA 02500	
		ZAROM	010	FACF	IF		FB				AA 02500	
		HUVSA	020	FAF	TF		FB	0.5	350.9 (345.9T)	006.9	AA 02500	
		YUTUC	021	SDF	TF		FB	0.3	350.9 (345.9T)	003.3	AA 01440	
		RW35	030	MAP	TF		FO	0.3	350.9 (345.9T)	002.1	AT 01180	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		350.9 (345.9T)		AA 01160	
	UTOTE	050		DF		FO				AA 03200	
	UTOTE	060		HM	R	FO		170.9 (165.9T)	004.0	AA 03200	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	HUVSA	N342403.10	W0824053.85	N3424.052	W08240.898
	UTOTE	N344153.98	W0824619.12	N3441.900	W08246.319
	WUPOX	N341848.24	W0823150.71	N3418.804	W08231.845
	YALBU	N341553.02	W0824553.64	N3415.884	W08245.894
	YUTUC	N342715.25	W0824152.05	N3427.254	W08241.868
	ZAROM	N341720.83	W0823852.30	N3417.347	W08238.872
	RW35	N342917.66	W0824229.17	N3429.294	W08242.486

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW35	00737	00

CITY AND STATE
ANDERSON, SC

ELEVATION: **782** **THRE: 737**
 AIRPORT NAME:
ANDERSON RGNL

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (GPS) RWY 35, AMDT 1
14 NOVEMBER 2013

SUP:
 AMDT: **ORIG**
 DATED: **03/15/2007**