

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
BUNKS	CAPOM (TF) (FB) (RNP 2.00)	234.93 / 43.15	3000
PYLER	TEPIE (TF) (FB) (RNP 2.00)	101.20 / 30.33	3000
CAPOM (IAF)	OSAME (NOPT) (TF) (FB) (RNP 1.00)	299.92 / 5.00	3000
TEPIE (IAF)	OSAME (NOPT) (TF) (FB) (RNP 1.00)	119.82 / 5.00	3000
OSAME (IF/IAF) (SEE FORM 8260-10)	CAMEA (TF) (FB) (RNP 1.00)	209.87 / 5.53	3000

LNAV: RW21

CLIMB TO 3000 DIRECT WELKI AND HOLD.

ADDITIONAL FLIGHT DATA:
HOLD SW, RT, 029.79 INBOUND.
CHART FAS OBST: 1506 TOWER 371246N/0920142W.
CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES.
CHART WEST PLAINS RGNL ASOS

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. **HOLD NE OSAME, RT, 209.87 INBOUND, 3000 FT. IN LIEU OF PT (IAF)**
3. FAC: 209.83 FAF: CAMEA DIST FAF TO MAP: 5.47 THLD: 5.47
4. MIN. ALT: **OSAME 3000, CAMEA 3000**
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: **20:1 IS NOT CLEAR 34:1 IS NOT CLEAR**
8. MSA FROM: **RW21 3100**

MAG VAR: 3E EPOCH YEAR: 1990

MINIMUMS

TAKEOFF: <u> </u> SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A <input checked="" type="checkbox"/>														
CATEGORY =====>															
	A	B	C	D	E										
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1960	1	740	1960	1	740		NA			NA				
CIRCLING	2020	1	800	2020	1 1/4	800		NA			NA				

NOTES:
CHART NOTE: PROCEDURE NA AT NIGHT.
CHART NOTE: USE WEST PLAINS ALTIMETER SETTING
CHART NOTE: RWY 21 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED
PBN REQUIREMENTS NOTE: RNP APCH



CITY AND STATE CABOOL, MO	ELEVATION: 1220 TDZE: 1220 AIRPORT NAME: CABOOL MEMORIAL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMD T NO./EFFECTIVE DATE: RNAV (GPS) RWY 21, ORIG-B 19 JULY 2018	SUP: AMD T: ORIG-A DATED 02/10/2011
-------------------------------------	---	-------------------------------------	---	---

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
CAMEA (FAF)	RW21 (MAP) (TF) (FO) (RNP 0.30)	209.83 / 5.47	
RW21 (MAP)	1620 MSL (CA)	209.83	
1620 MSL	WELKI (DF) (FO) (RNP 1.00)		3000



CITY AND STATE CABOOL, MO	ELEVATION: 1220 TDZE: 1220 AIRPORT NAME: CABOOL MEMORIAL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 21, ORIG-B 19 JULY 2018	SUP:
				AMDT: ORIG-A
				DATED: 02/10/2011