

**RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RBL VORTAC	TOWAN (TF) (FO) (RNP 2.00)	151.45 / 13.58	3500
HENLE	IMYIB (TF) (FB) (RNP 2.00)	075.94 / 6.55	5800
IMYIB (IAF)	TOWAN (NOPT) (TF) (FB) (RNP 1.00)	076.03 / 6.00	3500
GONGS (IAF)	TOWAN (NOPT) (TF) (FB) (RNP 1.00)	306.76 / 9.93	3500
TOWAN (IF/IAF) (SEE FORM 8260-10)	VIJIX (TF) (FB) (RNP 1.00)	331.16 / 11.29	2000

LPV: DA  
LNAV/VNAV: DA  
LNAV: RW33

CLIMB TO 4000 DIRECT PUVGE AND TRACK 028.09 TO HOMAN AND HOLD.

ADDITIONAL FLIGHT DATA:  
HOLD N, RT, 178.00 INBOUND.  
FAS OBST: 524 AAO 400512N/1221454W.  
DISTANCE TO THLD FROM 250 HAT: 0.69 NM.  
WAAS CHANNEL # 42609  
REFERENCE PATH ID: W33A  
CHART CIRCLING ICON.  
LTP HAE: 76.1 M

MAG VAR: 17E EPOCH YEAR: 1985

1. PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
2. HOLD SE TOWAN, RT, 331.16 INBOUND, 3500 FT. IN LIEU OF PT (IAF)
3. FAC: 331.12 FAF: VIJIX DIST FAF TO MAP: 5.01 THLD: 5.01
4. MIN. ALT: **TOWAN 3500, VIJIX 2000**
5. DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
6. MIN GS INCPT: 2000 GS ALT AT: VIJIX 2000 OM:        MM:        IM:
7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS CLEAR
8. MSA FROM: **RW33 9300**

**MINIMUMS**

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	602	1	250	602	1	250	602	1	250	602	1	250			
LNAV/VNAV DA	718	1 1/4	366	718	1 1/4	366	718	1 1/4	366	718	1 1/4	366			
LNAV MDA	780	1	428	780	1	428	780	1 1/4	428	780	1 1/2	428			
CIRCLING	860	1	508	860	1	508	900	1 1/2	548	1060	2 1/4	708			

NOTES:  
CHART NOTE: BARO-VNAV NA WHEN USING REDDING ALTIMETER SETTING.  
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F).  
CHART NOTE: DME/DME RNP-0.3 NA.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.



(CONTINUED ON PAGE 2)

CITY AND STATE <b>RED BLUFF, CA</b>	ELEVATION: 352 TDZE: 352 AIRPORT NAME: <b>RED BLUFF MUNI</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMD T NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 33, ORIG-A</b> 1 FEBRUARY 2018	SUP: AMDT: <b>ORIG</b> DATED <b>09/25/2008</b>
--	--	-------------------------------------	--	--

**US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES, (CONT.):**

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
VIJIX (FAF)	RW33 (MAP) (TF) (FO) (RNP 0.30)	331.12 / 5.01	
RW33 (MAP)	602 MSL (CA)	331.12	
602 MSL	PUVGE (DF) (FB) (RNP 1.00)		
PUVGE	HOMAN (TF) (FO) (RNP 1.00)	028.09 / 10.34	4000

**NOTES, (CONT.):**

**CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE REDDING ALTIMETER SETTING AND INCREASE ALL DA/MDA 80 FEET AND INCREASE LPV ALL CATS VISIBILITY 1/4 SM, LNAV/VNAV ALL CATS VISIBILITY 1/4 SM, LNAV CAT C VISIBILITY 1/4 SM AND CIRCLING CATS C AND D VISIBILITY 1/4 SM.**  
**CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON RBL VORTAC AIRWAY RADIALS 122 CW 185.**  
**CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT GONGS ON T261 SOUTHBOUND.**



CITY AND STATE <b>RED BLUFF, CA</b>	ELEVATION: 352 AIRPORT NAME: <b>RED BLUFF MUNI</b>	TDZE: 352	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 33, ORIG-A</b> 1 FEBRUARY 2018	SUP:
					AMDT: <b>ORIG</b>
					DATED: <b>09/25/2008</b>

**STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION**

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KRBL
RUNWAY	RW33
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W33A
LTP/FTP LATITUDE	400834.8685N
LTP/FTP LONGITUDE	1221500.7170W
LTP/FTP ELLIPSOIDAL HEIGHT	+00761
FPAP LATITUDE	401002.1270N
FPAP LONGITUDE	1221524.6240W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1096
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

**CRC REMAINDER** AABD2744

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+01048
FPAP ORTHOMETRIC HEIGHT	+01048



CITY AND STATE <b>RED BLUFF, CA</b>	ELEVATION: 352 TDZE: 352 AIRPORT NAME: <b>RED BLUFF MUNI</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 33, ORIG-A</b> 1 FEBRUARY 2018	SUP:
				AMDT: <b>ORIG</b>
				DATED: <b>09/25/2008</b>