

<b>U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</b> <b>VOR STANDARD INSTRUMENT APPROACH PROCEDURE</b> <b>FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23</b>								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 5.00 MILES AFTER FMG VORTAC OR AT BREAD/ 5.00 DME FIX  CLIMBING RIGHT TURN TO 10000 DIRECT FMG VORTAC AND HOLD, CONTINUE CLIMB-IN-HOLD TO 10000.  ADDITIONAL FLIGHT DATA: HOLD NE, LT, 221.13 INBOUND. FAS OBST: 5699 AAO 393136N/1194039W 6083 AAO 393157N/1193924W FAC 1969FT SOUTH OF RWY 16L THLD							
1. PT <u>R</u> SIDE OF COURSE <u>059.00</u> OUTBOUND <u>9300</u> FT WITHIN <u>10</u> MILES OF <u>FMG VORTAC</u> (IAF) 2. _____ 3. FAC <u>239.00</u> FAF <u>FMG VORTAC</u> DIST FAF TO MAP <u>5.00</u> THLD 4. MIN. ALT <u>FMG VORTAC 7800</u> 8. MSA FROM: <u>FMG VORTAC 130-250 12000, 250-350 10000, 350-130 9600</u>														MAG VAR: 16E		EPOCH YEAR: 1985	
<b>MINIMUMS</b>																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		@							
CATEGORY ==>		A			B			C			D			E			
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
CIRCLING		6000	1 1/4	1585	6000	1 1/2	1585	6000	3	1585	6000	3	1585				
NOTES: _____ @ CAT A, B 1600-2, CAT C, D 1600-3 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.																	
CITY AND STATE RENO, NV		ELEVATION: 4415 AIRPORT NAME:  RENO/TAHOE INTL		TDZE:		FACILITY IDENTIFIER: FMG		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR-D, AMDT 7 13 JAN 2011						SUP AMDT 6B DATE 03/11/2010			

