U.S. DEPARTMENT of TRANSPORTATION FEDERAL AVIATION ADMINISTRATION			DEPARTURE PROCEDURES / TAKEOFF MINIMUMS							
Bearings, headings, co otherwise indicated. C in feet RVR.	urses and radials are Ceilings are in feet ab	magnetic. El ove airport el	evations a evation. D	nd altitude Distances a	s are in fee re in nautio	et MSL. Al- cal miles, ex	titudes are m ccept visibilit	ninimum a ries which	ltitudes un are in sta	iless tute miles o
COORDINATED WITH										11
ATA AAT	ALPA APA	AOPA	NBAA		(specify)					
		X	X	X	ZOA ., 9	SAC APCH.	KO17 AMG	R.		I IN
TAKEOFF MINIM	UMS: RWY 7 NOT RWY 25 ST		D							100
F1-11-6-10										
IFR DEPARTURE	PROCEDURE:	RWY 25, CLII	MB VIA M	YV R-058	О 6000 Т	HEN CONT	INUE CLIMB	ON COU	RSE.	
787 25										
The m										
	la mai									
TAKEOFF OBSTA	CLES:			7	EPARTU 362 L/O T	OWER 392	TACLES: 330/120364	0		
STATE OF STATE										

DEVELOPED BY	APPROVED BY				
SIGNATURE: HOB J HALL	DATE: 03/21/97 FIFO: SAC FPO	SIGNATURE WILLIAM K.	Mensissen	ATE: 8/29/97 FO: AVN-120	
CITY AND STATE  GRASS VALLEY, CA	AIRPORT NEVADA	COUNTY AIR PARK	1 JAN 98	AMDT. NO.	