

TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 18, 36 NA-ENVIRONMENTAL.

RWY 4, 13 STANDARD.

RWY 22, 200-1 1/2 OR STANDARD WITH MINIMUM CLIMB OF 436 FEET PER NM TO 900.

RWY 31, 300-1 1/2 OR STANDARD WITH MINIMUM CLIMB OF 217 FEET PER NM TO 900, OR ALTERNATIVELY, WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT/NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1,700 FT PRIOR TO DEPARTURE END OF RUNWAY.

(2) TEXTUAL DEPARTURE PROCEDURE:

(3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 22, TREE 3,637' FROM DER, 985' RIGHT OF CENTERLINE, 100' AGL/809' MSL.

NOTE: RWY 31, TREE 7,679' FROM DER, 851' LEFT OF CENTERLINE, 100' AGL/819' MSL.

(4) CONTROLLING OBSTACLES:

RWY 22: 809 MSL TREE 353907.00N/0952257.00W

RWY 31: 819 MSL TREE 354027.00N/0952315.00W

(5) City, State

MUSKOGEE, OK

(6) Airport

DAVIS FIELD

(7) Effective Date

31 JUL 2008

(8) Amdt. No.

ORIG