

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION						RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.					
TERMINAL ROUTES												MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		RNP: DA CLIMB TO 5000 ON TRACK 123.20 TO FONTI AND HOLD, CONTINUE CLIMB-IN-HOLD TO 5000. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 309.40 INBOUND. ROUTE TYPE: A, H ROUTE TYPE QUALIFIER 1: F ROUTE TYPE QUALIFIER 2: S DISTANCE TO THLD FROM 458 HAT: 1.27 NM. #TCH 594.2 (DO NOT CHART) CHART MANDATORY 7000 AT STAAN CHART AT OR ABOVE 5000 AT RRIPP AND HRBEE CHART AT OR ABOVE 6000 AT JACSN CHART AT OR ABOVE 8000, AT OR BELOW 9000 AT VEEGE CHART PLANVIEW NOTE: RADAR REQUIRED							
STAAN (IAF)		KARRP (TF) (FB) (RNP 1.00)		083.65 / 5.53				6000									
KARRP		AARBY (TF) (FB) (RNP 1.00)		083.70 / 4.21				4000									
AARBY (IF)		FAULK (TF) (FB) (RNP 1.00)		085.27 / 6.80				3000									
JACSN (IAF)		PAULY (TF) (FB) (RNP 1.00)		122.95 / 3.14				5000									
PAULY		NAIRN (TF) (FB) (RNP 1.00)		123.00 / 5.34				3600									
(SEE FORM 8260-10)																	
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT HOPWD _____ 3. FAC: <u>123.15</u> FAF: _____ DIST FAF TO MAP: _____ THLD: _____ 4. MIN. ALT: HOPWD 1700 5. DIST TO THLD FROM OM: <u>3.47</u> MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: <u>1700</u> GS ALT AT: HOPWD 1700 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: <u>3.00</u> TCH: <u>54.4</u> # <u>20:1 IS CLEAR</u> <u>34:1 IS NOT CLEAR</u> 8. MSA FROM: RW12R 3000																	
												MAG VAR: 1W EPOCH YEAR: 2020					
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD					
CATEGORY =====>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
AUTHORIZATION REQUIRED																	
RNP 0.30 DA	998	6000	458	998	6000	458	998	6000	458	998	6000	458					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -16C (4F) OR ABOVE 54C (130F). CHART NOTE: GPS REQUIRED. CHART SPEED ICON IN PLANVIEW AT DUZER : MAX 210 KIAS. CHART SPEED ICON IN PLANVIEW AT KLISH : MAX 180 KIAS. (CONTINUED ON PAGE 2)																	
CITY AND STATE		ELEVATION: 618 TDZE: 540				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:						SUP:			
ST LOUIS, MO		AIRPORT NAME:				RNAV		RNAV (RNP) Z RWY 12R, ORIG-C						AMDT: ORIG-B			
		ST LOUIS LAMBERT INTL						29 MARCH 2018						DATED 08/17/2017			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33				
TERMINAL ROUTES, (CONT.):				
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
NAIRN	FAULK (TF) (FB) (RNP 1.00)	123.07 / 2.19	3000	
VEEGE (IAF)	YADDI (TF) (FB) (RNP 1.00)	148.06 / 10.27	5500	
YADDI	CORDL (TF) (FB) (RNP 1.00)	148.13 / 5.70	4000	
CORDL (IF)	FAULK (TF) (FB) (RNP 1.00)	149.80 / 6.35	3000	
FAULK	KLISH (TF) (FB) (RNP 1.00)	123.06 / 2.83	2300	
RRIPP (IF)	DUZER (TF) (FB) (RNP 1.00)	302.79 / 2.91	5000	
DUZER	KLISH (RF) (FB) (RNP 1.00)	(2.50 NM RADIUS CW (CFBPW))/7.87	2300	
HRBEE (IF)	BUFEE (TF) (FB) (RNP 1.00)	301.32 / 2.89	5000	
BUFEE	KLISH (RF) (FB) (RNP 1.00)	(2.91 NM RADIUS CCW (CFBPZ))/9.04	2300	
KLISH	HOPWD (TF) (FB) (RNP 1.00)	123.13 / 2.11	1700	
HOPWD (FAF)	RW12R (MAP) (TF) (FO) (RNP 0.30)	123.15 / 3.47		
RW12R (MAP)	FONTI (TF) (FO) (RNP 1.00)	123.20 / 12.97	5000	
NOTES, (CONT.): CHART SPEED ICON IN PLANVIEW AT BUFEE : MAX 210 KIAS. CHART PLANVIEW NOTE ADJACENT TO RRIPP IF: RF REQUIRED. CHART PLANVIEW NOTE ADJACENT TO HRBEE IF: RF REQUIRED. CHART NOTE: FOR INOPERATIVE ALS, INCREASE RNP 0.30 ALL CATS VISIBILITY TO 1 1/2 SM. CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED WITH RWY 11, EXCEPT FOR ARRIVALS AT RRIPP AND HRBEE. CHART NOTE: USE OF FD OR AP REQUIRED DURING SIMULTANEOUS OPERATIONS. CHART PROFILE NOTE: SEE PLANVIEW FOR MULTIPLE IF LOCATIONS.				
CITY AND STATE	ELEVATION: 618	TDZE: 540	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
ST LOUIS, MO	AIRPORT NAME:		RNAV	RNAV (RNP) Z RWY 12R, ORIG-C
	ST LOUIS LAMBERT INTL			29 MARCH 2018
			SUP:	
			AMDT:	ORIG-B
			DATED:	08/17/2017

