

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES											MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW02 CLIMB TO 650 THEN CLIMBING RIGHT TURN TO 6000 DIRECT MRGGO AND HOLD, CONTINUE CLIMB-IN-HOLD TO 6000. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 304.46 INBOUND. CHART FAS OBST: 253 TREE 392845N/1213805W DISTANCE TO THLD FROM 250 HAT: 0.66 NM. CHART VDP AT 0.93 NM TO RW02* *LNAV ONLY. WAAS CHANNEL # 49026 REFERENCE PATH ID: W02A CHART CIRCLING ICON. LTP HAE: 27.3 M							
MRGGO		ESVOW (TF) (FO) (RNP 2.00)			267.38 / 23.56			3600									
YUBBA (IAF)		ESVOW (NOPT) (TF) (FB) (RNP 1.00)			343.65 / 11.29			3600									
ESVOW (IF/IAF)		IXACE (TF) (FB) (RNP 1.00)			016.88 / 6.00			2100									
IXACE (FAF)		VIGCE/1.90 NM TO RW02 (TF) (FB) (RNP 0.30)			016.93 / 4.00												
VIGCE/1.90 NM TO RW02		RW02 (MAP) (TF) (FO) (RNP 0.30)			016.93 / 1.90												
(SEE FORM 8260-10)																	
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S ESVOW, RT, 016.88 INBOUND, 3600 FT. IN LIEU OF PT (IAF) 3. FAC: 016.93 FAF: IXACE DIST FAF TO MAP: 5.90 THLD: 5.90 4. MIN. ALT: ESVOW 3600, IXACE 2100, VIGCE/1.90 NM TO RW02 820* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2100 GS ALT AT: IXACE 2100 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS CLEAR 8. MSA FROM: RW02 7400																	
											MAG VAR: 16E					EPOCH YEAR: 1990	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD								
CATEGORY =====>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LPV DA	432	7/8	250	432	7/8	250	432	7/8	250	432	7/8	250					
LNAV/VNAV DA	432	7/8	250	432	7/8	250	432	7/8	250	432	7/8	250					
LNAV MDA	520	1	338	520	1	338	520	1	338	520	1	338					
CIRCLING	580	1	386	660	1	466	660	1 1/2	466	780	2	586					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -2C (29F) OR ABOVE 54C (130F). CHART NOTE: CIRCLING NA NE OF RWY 13-31. CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT MRGGO ON V332 SOUTHEASTBOUND, AND ARRIVALS AT YUBBA ON V23 SOUTHBOUND.																	
CITY AND STATE		ELEVATION: 194 TDZE: 182			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:					SUP:				
OROVILLE, CA		AIRPORT NAME:			OROVILLE MUNI			RNAV (GPS) RWY 2, AMDT 1					AMDT: ORIG-C				
								22 JUNE 2017					DATED 10/15/2015				



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW02 (MAP)	650 MSL (CA)	016.93	
650 MSL	MRGGO (DF) (FO) (RNP 1.00)		6000

QUALITY
18
CHECKED

CITY AND STATE
OROVILLE, CA

ELEVATION: 194 TDZE: 182
AIRPORT NAME:
OROVILLE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 2, AMDT 1
22 JUNE 2017

SUP:
AMDT: ORIG-C
DATED: 10/15/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KOVE
RUNWAY	RW02
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W02A
LTP/FTP LATITUDE	392843.8560N
LTP/FTP LONGITUDE	1213754.5110W
LTP/FTP ELLIPSOIDAL HEIGHT	+00273
FPAP LATITUDE	392958.6600N
FPAP LONGITUDE	1213651.8700W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0912
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

95FA246F

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+00553
FPAP ORTHOMETRIC HEIGHT	+00553

QUALITY
18
CHECKED

CITY AND STATE

OROVILLE, CA

ELEVATION: 194

TDZE: 182

AIRPORT NAME:

OROVILLE MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 2, AMDT 1

22 JUNE 2017

SUP:

AMDT: ORIG-C

DATED: 10/15/2015