

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)
TITLE 14 CFR PART 97.37**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>CITY, STATE</u>	<u>AIRPORT</u>	<u>EFFECTIVE DATE</u>	<u>AMDT NO</u>
SPRINGFIELD, CO	SPRINGFIELD MUNI	24 MAY 2018	ORIG-A

TAKEOFF MINIMUMS:

RWY 35, STANDARD.

RWY 17, 500-3 OR STANDARD WITH A MINIMUM CLIMB OF 220 FT PER NM TO 5000.

TEXTUAL DEPARTURE PROCEDURES:

VISUAL CLIMB OVER AIRPORT:

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 17: TERRAIN 2 FT FROM DER, 148 FT RIGHT OF CENTERLINE, 4388 FT MSL. POLE, VERTICAL POINT BEGINNING 9 FT FROM DER, 9 FT LEFT OF CENTERLINE, UP TO 4390 FT MSL. FENCE 17 FT FROM DER, 445 FT RIGHT OF CENTERLINE, 3 FT AGL/4396 FT MSL. VEHICLE ON ROAD, TERRAIN BEGINNING 134 FT FROM DER, 494 FT RIGHT OF CENTERLINE, UP TO 4410 FT MSL. POLES, TANK BEGINNING 403 FT FROM DER, 581 FT RIGHT OF CENTERLINE, UP TO 30 FT AGL/4425 FT MSL. ANTENNA 2.5 NM FROM DER, 2924 FT RIGHT OF CENTERLINE, UP TO 30 FT AGL/4425 FT MSL. TOWER 2.5 NM FROM DER, 2923 FT RIGHT OF CENTERLINE, 417 FT AGL/4802 FT MSL.

NOTE: RWY 35: POLE 9 FT FROM DER, 10 FT RIGHT OF CENTERLINE, 3 FT AGL/4392 FT MSL. FENCE 117 FT FROM DER, 446 FT LEFT OF CENTERLINE, 3 FT AGL/4394 FT MSL. VEHICLE ON ROAD 222 FT FROM DER, 546 FT LEFT OF CENTERLINE, 4408 FT MSL. POLES BEGINNING 539 FT FROM DER, 622 FT LEFT OF CENTERLINE, UP TO 28 FT AGL/4420 FT MSL. POLE 1195 FT FROM DER, 623 FT LEFT OF CENTERLINE, 29 FT AGL/4421 FT MSL.

CONTROLLING OBSTACLES:

RWY 17: 4802 FEET MSL TOWER 372436.14N/1023738.84W



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)
TITLE 14 CFR PART 97.37**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>CITY, STATE</u>	<u>AIRPORT</u>	<u>EFFECTIVE DATE</u>	<u>AMDT NO</u>
SPRINGFIELD, CO	SPRINGFIELD MUNI	24 MAY 2018	ORIG-A

REMARKS:

FLIGHT INSPECTED BY:

FLIGHT INSEPCTION NOT REQUIRED PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-333) MEMO DEC 22, 2017

OFFICE SYMBOL:

DATE:

Digitally signed by

BEV L BORDY

Mar 22, 2018

DEVELOPED BY:

VICTOR B. NASO (BRENT WEATHERS)

Digitally signed by

BEV L BORDY

Mar 22, 2018

OFFICE SYMBOL:

AJV-5413

DATE:

11/13/2017

APPROVED BY:

GEORGE E. DAVIS

Digitally signed by

BEV L BORDY

Mar 22, 2018

OFFICE SYMBOL:

AJV-5410

DATE:

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

A4A

ALPA

AOPA

APA

HAI

NBAA



OTHER:

CHANGES - REASONS:

1. CHANGED TAKEOFF MINIMUMS RWY 17 FROM "4900-3 OR STANDARD WITH MINIMUM CLIMB OF 225 FEET PER NM TO 5000" TO "500-3 OR STANDARD WITH MINIMUM CLIMB OF 220 FEET PER NM TO 5000" DUE TO INCORRECT CEILING COMPUTATION AND NEW SURVEY (SAME CONTROLLING OBSTRUCTION WITH ELEVATION LOWERED 15' AND COORDINATES MOVED 19.6').
2. UPDATED TAKEOFF OBSTACLE NOTES DUE TO NEW SURVEY.

QUALITY
8
CHECKED