

PAGE 1 OF 6 PAGES

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (RNP) - STANDARD,
INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
CLFFF (IF)	CEPEE (TF) (FB) (RNP 1.00)	352.54 / 3.57	10000
CEPEE	AAGEE (RF) (FB) (RNP 1.00)	(2.75 NM RADIUS CW (CFNRL)/4.31	8700
AAGEE	LINTE (TF) (FB) (RNP 1.00)	082.49 / 1.51	8300
LINTE	LEETS (RF) (FB) (RNP 1.00)	(2.77 NM RADIUS CW (CFNRP)/4.35	7000
LEETS (FAF)	RW16L (MAP) (TF) (FO)	172.51 / 4.99	
RW16L (MAP)	5900 MSL (CA)	172.51	5900
5900 MSL	BINBE (DF) (FO)		10000

NOTES, (CONT.):

CHART PLANVIEW NOTE ADJACENT TO QWIK: RF REQUIRED.

CHART PLANVIEW NOTE ADJACENT TO CLFFF: RF REQUIRED.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

CHART NOTE: FOR INOPERATIVE MALSR, INCREASE RNP 0.10 ALL CATS VISIBILITY TO RVR 4000 AND RNP 0.30

ALL CATS VISIBILITY TO RVR 5000

CHART PROFILE NOTE: SEE PLANVIEW FOR MULTIPLE IF LOCATIONS

CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED WITH RWY 17L AND 17R, EXCEPT FOR ARRIVALS AT QWIK AND CLFFF

CHART PLANVIEW NOTE AT QWIK: MAX 210 KIAS

CHART PLANVIEW NOTE AT CLFFF: MAX 210 KIAS

CHART NOTE: USE OF FD OR AP PROVIDING RNAV TRACK GUIDANCE REQUIRED DURING SIMULTANEOUS OPERATIONS

CITY AND STATE
DENVER, CO

ELEVATION: 5434 THRE: 5350
AIRPORT NAME:
DENVER INTL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (RNP) Z RWY 16L, ORIG
15 NOVEMBER 2012

SUP:
AMDT: NONE
DATED:

RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (RNP)

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KDENK2FH16LZ	ACLFFF	010CLFFFK2EA0E	B	IF				11000	18000210		A-FS	
SUSAP	KDENK2FH16LZ	ACLFFF	020CEPEEK2EA0E		010TF				+ 10000			A FS	
SUSAP	KDENK2FH16LZ	ACLFFF	030AAGEEK2EA0E	R010RF		0027503525	08250043		+ 08700		CFNRL K2EAA	FS	
SUSAP	KDENK2FH16LZ	ACLFFF	040LINTSK2EA0E		010TF				+ 08300			A FS	
SUSAP	KDENK2FH16LZ	ACLFFF	050LEETSK2EA0EE	R010RF		0027700825	17250044		+ 07000		CFNRP K2EAA	FS	
SUSAP	KDENK2FH16LZ	AJOB0B	010JOB0BK2EA0E	B	IF					18000		A FS	
SUSAP	KDENK2FH16LZ	AJOB0B	020LEETSK2EA0EE		010TF				+ 07000			A FS	
SUSAP	KDENK2FH16LZ	AQWIKE	010QWIKEK2EA0E	B	IF				11000	18000210		A-FS	
SUSAP	KDENK2FH16LZ	AQWIKE	020STAAMK2EA0E		010TF				+ 10000			A FS	
SUSAP	KDENK2FH16LZ	AQWIKE	030DAVTEK2EA0E	L010RF		0027403526	26260043		+ 09000		CFPQC K2EAA	FS	
SUSAP	KDENK2FH16LZ	AQWIKE	040LAAAKK2EA0E		010TF				+ 08400			A FS	
SUSAP	KDENK2FH16LZ	AQWIKE	050LEETSK2EA0EE	L010RF		0029202626	17250046		+ 07000		CFPPZ K2EAA	FS	
SUSAP	KDENK2FH16LZ	H	020LEETSK2EA1E	F	IF				+ 07000	18000	RW16LBK2PGA	FS	
SUSAP	KDENK2FH16LZ	H	020LEETSK2EA2W							A031A011		FS	
SUSAP	KDENK2FH16LZ	H	030RW16LK2PG0GY	M	031TF				05410	-300		A FS	
SUSAP	KDENK2FH16LZ	H	040		0 M		1725		+ 05900			A FS	
SUSAP	KDENK2FH16LZ	H	050BINBEK2EA0EY		DF				+ 10000			A FS	

CITY AND STATE
DENVER, CO

ELEVATION: 5434 THRE: 5350
AIRPORT NAME: DENVER INTL

FACILITY
IDENTIFIER:
| RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (RNP) Z RWY 16L, ORIG
15 NOVEMBER 2012

SUP:	
AMDT:	NONE
DATED:	

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

A FS

SUSAP KDENK2GRW16L 0120001725 N39534933W104411250+0000 +1612505350000060150IILTT1

SUSAP KDENK2SRW16LK2PGB 0 18018010325 M

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (RNP)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	CLFFF	CLFFF	010		IF		FB				AT 11000	AB 210
	CLFFF	CEPEE	020		TF		FB	1.0			AA 10000	
	CLFFF	AAGEE	030		RF	R	FB	1.0		004.3	AA 08700	
	CLFFF	LINTE	040		TF		FB	1.0			AA 08300	
	CLFFF	LEETS	050		RF	R	FB	1.0		004.4	AA 07000	
	JOBBOB	JOBBOB	010		IF		FB					
	JOBBOB	LEETS	020		TF		FB	1.0			AA 07000	
	QWIKE	QWIKE	010		IF		FB				AT 11000	AB 210
	QWIKE	STAAM	020		TF		FB	1.0			AA 10000	
	QWIKE	DAVTE	030		RF	L	FB	1.0		004.3	AA 09000	
	QWIKE	LAAAK	040		TF		FB	1.0			AA 08400	
	QWIKE	LEETS	050		RF	L	FB	1.0		004.6	AA 07000	
		LEETS	020	FAF	IF		FB				AA 07000	
		RW16L	030	MAP	TF		FO	0.3			AT 05410	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		172.5 (180.5T)		AA 05900	
	BINBE	050		DF		FO				AA 10000	
	BINBE	060		HM	R	FO		257.5 (265.5T)	007.0	AA 10000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	AAGEE	N400137.71	W1044641.74	N4001.629	W10446.696
	BINBE	N394010.74	W1045650.55	N3940.179	W10456.843
	CEPEE	N395854.34	W1045017.93	N3958.906	W10450.299
	CFNRL	N395852.81	W1044643.57	N3958.880	W10446.726
	CFNRP	N395850.48	W1044445.39	N3958.841	W10444.757
	CFPPZ	N395847.43	W1043720.98	N3958.791	W10437.350
	CFPQC	N395857.28	W1043449.74	N3958.955	W10434.829
	CLFFF	N395520.10	W1045020.55	N3955.335	W10450.343
	DAVTE	N400141.70	W1043447.54	N4001.695	W10434.792
	JOBBOB	N400941.94	W1044101.45	N4009.699	W10441.024
	LAAAK	N400142.87	W1043718.82	N4001.715	W10437.314
	LEETS	N395849.05	W1044109.03	N3958.818	W10441.151
	LINTE	N400136.92	W1044443.46	N4001.615	W10444.724
	QWIKE	N395555.43	W1043118.56	N3955.924	W10431.309
	STAAM	N395855.54	W1043116.01	N3958.926	W10431.267
	RW16L	N395349.33	W1044112.50	N3953.822	W10441.208

RUNWAY DATA	THRESHOLD	TCH
RWY	ELEVATION	

CITY AND STATE
DENVER, CO

ELEVATION: 5434 THRE: 5350
 AIRPORT NAME:
 DENVER INTL

FACILITY
IDENTIFIER:
 RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
 RNAV (RNP) Z RWY 16L, ORIG
 15 NOVEMBER 2012

SUP:
 AMDT: NONE
 DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

RW16L 05350 60

CITY AND STATE
DENVER, CO

ELEVATION: 5434 THRE: 5350
AIRPORT NAME:
DENVER INTL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (RNP) Z RWY 16L, ORIG
15 NOVEMBER 2012

SUP:
AMDT: NONE
DATED: