

RNAV - STANDARD US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION						INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES																MISSED APPROACH									
FROM				TO				COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW27 CLIMB TO 500 THEN CLIMBING LEFT TURN TO 2000 DIRECT LAMRE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 360.00 INBOUND. CHART FAS OBST: 130 TREE 262540N/0812330W DISTANCE TO THLD FROM 250 HAT: 0.62 NM. CHART VDP AT 0.92 NM TO RW27* *LNAV ONLY. WAAS CHANNEL # 69613 REFERENCE PATH ID: W27A CHART CIRCLING ICON. LTP HAE: -14.1 M											
WIXUX (IAF)				ZUGDU (NOPT) (TF) (FB) (RNP 1.00)				003.12 / 8.00				2900													
JEXQU (IAF)				ZUGDU (NOPT) (TF) (FB) (RNP 1.00)				183.12 / 8.00				2900													
ZUGDU (IF/IAF)				UXUVE (TF) (FB) (RNP 1.00)				273.12 / 6.87				1700													
UXUVE (FAF)				IXIVE/2.50 NM TO RW27 (TF) (FB) (RNP 0.30)				273.06 / 2.57																	
IXIVE/2.50 NM TO RW27				RW27 (MAP) (TF) (FO) (RNP 0.30)				273.06 / 2.50																	
(SEE FORM 8260-10)																									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD E ZUGDU, RT, 273.12 INBOUND, 2900 FT. IN LIEU OF PT (IAF) 3. FAC: 273.06 FAF: UXUVE DIST FAF TO MAP: 5.07 THLD: 5.07 4. MIN. ALT: ZUGDU 2900, UXUVE 1700, IXIVE/2.50 NM TO RW27 880* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 1700 GS ALT AT: UXUVE 1700 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 52.5 34:1 IS CLEAR 8. MSA FROM: _____																MAG VAR: 5W EPOCH YEAR: 2010									
MINIMUMS																									
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD															
CATEGORY ==>		A			B			C			D			E											
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA										
LPV DA	285	3/4	250	285	3/4	250	285	3/4	250	285	3/4	250													
LNAV/VNAV DA	311	7/8	276	311	7/8	276	311	7/8	276	311	7/8	276													
LNAV MDA	380	1	345	380	1	345	380	1	345	380	1	345													
CIRCLING	500	1	463	640	1	603	640	1 3/4	603	680	2	643													
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW 0C (32F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA.																									
CITY AND STATE				ELEVATION: 37 TDZE: 35				FACILITY IDENTIFIER:				PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:									
IMMOKALEE, FL				AIRPORT NAME:				RNAV				RNAV (GPS) RWY 27, AMDT 1				AMDT: ORIG-B									
				IMMOKALEE RGNL								17 AUGUST 2017				DATED 08/21/2014									

QUALITY
 10
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW27 (MAP)	500 MSL (CA)	273.06	500

500 MSL	LAMRE (DF) (FO) (RNP 1.00)		2000
---------	----------------------------	--	------

TAA

	FROM	TO	ALT
1.	183/30 CW 003/30 (NOPT)	ZUGDU (IF/IAF) (FB)	2900
2.	003/30 CW 093/30	WIXUX (IAF) (FB)	2900
3.	093/30 CW 183/30	JEXQU (IAF) (FB)	2900

CITY AND STATE
IMMOKALEE, FL

ELEVATION: 37 TDZE: 35
AIRPORT NAME:
IMMOKALEE RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 27, AMDT 1
17 AUGUST 2017

SUP:
AMDT: ORIG-B
DATED: 08/21/2014

QUALITY
10
CHECKED

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KIMM
RUNWAY	RW27
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W27A
LTP/FTP LATITUDE	262615.1750N
LTP/FTP LONGITUDE	0812319.6535W
LTP/FTP ELLIPSOIDAL HEIGHT	-00141
FPAP LATITUDE	262612.0770N
FPAP LONGITUDE	0812458.8555W
THRESHOLD CROSSING HEIGHT (TCH)	00052.5
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1232
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 0A701653

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00104
FPAP ORTHOMETRIC HEIGHT	+00104

QUALITY
10
CHECKED

CITY AND STATE IMMOKALEE, FL	ELEVATION: 37 AIRPORT NAME: IMMOKALEE RGNL	TDZE: 35	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 27, AMDT 1 17 AUGUST 2017	SUP:
					AMDT: ORIG-B
					DATED: 08/21/2014