

**RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE	
JICTI	PAPDE (TF) (FB) (RNP 2.00)	206.25 / 12.30	2300	<b>LPV: DA</b> <b>LNAV/VNAV: DA</b> <b>LNAV: RW09</b>  <b>CLIMB TO 500 THEN CLIMBING LEFT TURN TO 2000 DIRECT JABMA AND HOLD.</b>  <b>ADDITIONAL FLIGHT DATA:</b> <b>HOLD N, RT, 180.00 INBOUND.</b> <b>CHART FAS OBST: 186 POLE 262603N/0812607W</b> <b>DISTANCE TO THLD FROM 250 HAT: 0.62 NM.</b> <b>WAAS CHANNEL # 99713</b> <b>REFERENCE PATH ID: W09A</b> <b>CHART CIRCLING ICON.</b> <b>LTP HAE: -13.1 M</b>
MILES	OBMEE (TF) (FB) (RNP 2.00)	051.08 / 7.23	2300	
PAPDE (IAF)	FAPTO (TF) (FB) (RNP 1.00)	182.93 / 5.80	2300	
OBMEE (IAF)	FAPTO (TF) (FB) (RNP 1.00)	002.93 / 5.80	2300	
FAPTO (IF)	ECAMO (TF) (FB) (RNP 1.00)	092.92 / 5.80	1800	
(SEE FORM 8260-10)				

1. PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
2. PROFILE STARTS AT FAPTO
3. FAC: 092.99 FAF: ECAMO DIST FAF TO MAP: 5.37 THLD: 5.37
4. MIN. ALT: FAPTO 2300, ECAMO 1800, RADVE/1.50 NM TO RW09 560\*
5. DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
6. MIN GS INCPT: 1800 GS ALT AT: ECAMO 1800 OM:        MM:        IM:
7. GS ANGLE: 3.00 TCH: 51.8 34:1 IS CLEAR
8. MSA FROM: RW09 2300

MAG VAR: **5W** EPOCH YEAR: **2010**

**MINIMUMS**

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD					
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	287	3/4	250	287	3/4	250	287	3/4	250	287	3/4	250			
LNAV/VNAV DA	287	3/4	250	287	3/4	250	287	3/4	250	287	3/4	250			
LNAV MDA	440	1	403	440	1	403	440	1 1/8	403	440	1 1/8	403			
CIRCLING	500	1	463	640	1	603	640	1 3/4	603	680	2	643			

NOTES:  
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW 0C (32F) OR ABOVE 54C (130F).  
 CHART NOTE: DME/DME RNP-0.3 NA.  
 \*LNAV ONLY  
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT JICTI ON V225 NORTHEAST BOUND.  
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT MILES ON V539 SOUTHBOUND.



CITY AND STATE <b>IMMOKALEE, FL</b>	ELEVATION: <b>37</b> TDZE: <b>37</b> AIRPORT NAME: <b>IMMOKALEE RGNL</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 9, AMDT 1</b> <b>17 AUGUST 2017</b>	SUP: AMDT: <b>ORIG-B</b> DATED <b>08/21/2014</b>
--	--	-------------------------------------	--	--

**US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES, (CONT.):**

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
ECAMO (FAF)	RADVE/1.50 NM TO RW09 (TF) (FB) (RNP 0.30)	092.99 / 3.87	
RADVE/1.50 NM TO RW09	RW09 (MAP) (TF) (FO) (RNP 0.30)	092.99 / 1.50	
RW09 (MAP)	500 MSL (CA)	092.99	500
500 MSL	JABMA (DF) (FO) (RNP 1.00)		2000

QUALITY  
10  
CHECKED

CITY AND STATE <b>IMMOKALEE, FL</b>	ELEVATION: 37 TDZE: 37 AIRPORT NAME: <b>IMMOKALEE RGNL</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 9, AMDT 1</b> 17 AUGUST 2017	SUP:
				AMDT: <b>ORIG-B</b>
				DATED: <b>08/21/2014</b>

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KIMM
RUNWAY	RW09
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W09A
LTP/FTP LATITUDE	262613.4765N
LTP/FTP LONGITUDE	0812414.6280W
LTP/FTP ELLIPSOIDAL HEIGHT	-00131
FPAP LATITUDE	262616.5375N
FPAP LONGITUDE	0812235.4250W
THRESHOLD CROSSING HEIGHT (TCH)	00051.8
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
<u>CRC REMAINDER</u>	19262EB5

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00113
FPAP ORTHOMETRIC HEIGHT	+00113

QUALITY  
10  
CHECKED

CITY AND STATE <b>IMMOKALEE, FL</b>	<b>ELEVATION: 37</b>	<b>TDZE: 37</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 9, AMDT 1</b> 17 AUGUST 2017	SUP:	
	AIRPORT NAME: <b>IMMOKALEE RGNL</b>				AMDT:	<b>ORIG-B</b>
					DATED:	<b>08/21/2014</b>