FEDERAL AVIATION ADMINISTRATION

FLIGHT STANDARDS SERVICE

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE

TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

AIRPOR		PROCEDURE NAME	ORIGINAL/AMENDMENT	I <u>CITY</u>	STATE
HAMPTON ROADS		RNAV (GPS) RWY 28	ORIG	NORFOLK	VA
AIRPORT ELEVATION	<u>TDZE</u>	SUPERSEDED	ORIGINAL/AMENDMENT	DATED MAG VAR	EPOCH YEAR
28	25		NONE	10W	2000
FACILITY RNAV	COORDINATES OF FACILITIES	ACTUAL EFFECTIVE DATE 15 AUGUST 2019	REQUIRED EFFECTIVE DATE ROUTINE	CANCEL/SUSPEND	

TERMINAL ROUTES

FROM	FIX TYPE	<u>T0</u>	FIX TYPE	LEG TYPE	FO/FB	<u>RNP</u>	COURSE	DISTANCE	ALTITUDE
FOXEI	IF	JAJAE		TF	FB	1.00	282.56	6.19	1600
JAJAE	FAF	YINUK/2.40 NM TO RW28		TF	FB	0.30	282.48	2.41	
YINUK/2.40 NM TO RW28		RW28	MAP	TF	FO	0.30	282.48	2.40	
RW28	MAP	1600 MSL		CA			282.48		1600
1600 MSL		PSALM		DF	FO	1.00			2500

MISSED APPROACH

MAP:

LNAV: RW28

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 1600 THEN CLIMBING LEFT TURN TO 2500 DIRECT PSALM AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:	<u>.</u>								
1. PT	SIDE OF COURSE	OUTBOUND		FT WITHIN	MILES	OF (IAF)			
2. PROF	ILE STARTS AT FOXEI								
3. FAC:	282.48 FAF: JAJAE	E D'	IST FAF	TO MAP: 4.81		DIST FAF TO TH	LD: 4.81		
4. MIN AL	.T: FOXEI 2000, JAJAE	1600, YINUK/2.40 NM TO F	२W28 820	D					
5. DIST T	O THLD FROM OM:	MM:	IM:	150 HAT:	GS	SANT:			
6. MIN GP	' INCPT:	GP ALT AT FAF :				OM:	MM:	IM:	
7. GP ANG	GLE:	34:1: IS NOT CLEAR	20:1:	IS CLEAR	TCH:				
8. MSA FI	ROM: RW28 2300								



AIRPORT	AIRPORT ID	PROCEDURE NAME	ORIGINAL/AMENDMENT	CITY	STATE
HAMPTON ROADS EXECUTIVE	KPVG	RNAV (GPS) RWY 28	ORIG	NORFOLK	VA

PBN REQUIREMENTS NOTE:

RNP APCH.

NOTES:

CHART NOTE: CIRCLING NA TO RWYS 2 AND 20. CHART NOTE: CIRCLING CAT C NA N OF RWY 10-28. CHART NOTE: RWY 28 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

ADDITIONAL FLIGHT DATA:

CHART CIRCLING ICON. CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES. CHART VDP AT 1.23 NM TO RW28 CHART FAS OBST: 192 TOWER 364656N/0762510W. HOLD SW, RT, 056.39 INBOUND

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA

STANDARD

CATEGORY:		Α			В			С			D			Е	
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LNAV MDA	460	1	435	460	1	435	460	1 1/4	435		NA				
CIRCLING	500	1	472	500	1	472	780	2	752		NA				

CHANGES - REASONS

05/06/19: THIS IS AN UPDATED COPY OF THE FORM DEVELOPED ON 04/03/19. I. ADDITIONAL FLIGHT DATA NOTE CHANGED FROM "YUKIN TO RW28: 3.00/45" TO "VISUAL SEGMENT - OBSTACLES.".

COORDINATED WITH:

	<u>HAI</u> <u>NBAA</u> X	OTHER: ZDC, ORF APP CON,	AMGR	
FLIGHT CHECKED BY JORGE ALBERTO MALCUN		Digitally signed by <u>OFFI</u> DAVID TEFFETELLER FIO May 07, 2019		
DEVELOPED BY FRANK MOORE	Digitally signed by FRANK MOORE	OFFI AJV-A Digitally signed by		
APPROVED BY PATRICK MULQUEEN	May 06, 2019	DAVID TEFFETELLER OFFI May 07, 2019 A4		<u>TITLE</u> MANAGER

WALIT. 7 CHECKE