FEDERAL AVIATION ADMINISTRATION

FLIGHT STANDARDS SERVICE VOR STANDARD INSTRUMENT APPROACH PROCEDURE

TITLE 14 CFR PART 97.23

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA, Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

AIRPORT AIRPORT ID **PROCEDURE NAME** ORIGINAL/AMENDMENT **STATE** CITY RALPH WIEN MEMORIAL **PAOT** VOR RWY 27 ORIG-B **KOTZEBUE** AK

AIRPORT ELEVATION **TDZE** ORIGINAL/AMENDMENT **EPOCH YEAR** SUPERSEDED DATED MAG VAR 15 15 VOR RWY 27 ORIG-A 12/07/2017 15E 2010

FACILITY COORDINATES OF FACILITIES ACTUAL EFFECTIVE DATE REQUIRED EFFECTIVE DATE CANCEL/SUSPEND OTZ ROUTINE

3 JANUARY 2019

TERMINAL ROUTES

THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 18-25.

FROM	FIX TYPE	<u>TO</u>	FIX TYPE	LEG TYPE	FO/FB	RNP	<u>COURSE</u>	DISTANCE	ALTITUDE
OTZ VOR/DME		LOTIC/3.50 DME	IAF				076.81	3.50	2500
JUMAS/12.00 DME CCW	IAF	ZOTOR/12.00 DME	NOPT				12.00 DME ARC (OTZ LR-087)		1600
MUNUE/12.00 DME CW	IAF	ZOTOR/12.00 DME	NOPT				12.00 DME ARC		1600
ZOTOR/12.00 DME	IF	LOTIC/3.50 DME					256.81	8.50 (OTZ R-077)	1600

MISSED APPROACH

MAP:

OTZ VOR/DME

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 1600 THEN CLIMBING LEFT TURN TO 2000 DIRECT OTZ VOR/DME AND HOLD, CONTINUE CLIMB-IN-HOLD TO 2000.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

SIDE OF COURSE 076.81 **OUTBOUND** 1600 FT WITHIN 10 MILES OF LOTIC/3.50 DME (IAF)

2.

3. FAC: 256.81 **DIST FAF TO MAP: DIST FAF TO THLD: 4.16** FAF: LOTIC/3.50 DME

4. MIN ALT: LOTIC/3.50 DME 1600, INIYU/1.70 DME 920

8. MSA FROM: OTZ VOR/DME 360-090 3700, 090-270 1600, 270-360 3300

EQUIPMENT REQUIREMENTS NOTES:

DME REQUIRED.

NOTES:

CHART NOTE: CIRCLING TO RWY 18, 36 NA AT NIGHT.

CHART NOTE: RWY 27 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART NOTE: STRAIGHT IN RWY 27 AT NIGHT, CIRCLING RWY 27 AT NIGHT, OPERATIONAL VGSI REQUIRED, REMAIN ON OR ABOVE GLIDEPATH UNTIL THRESHOLD.

	<u>PORT</u> N MEMORIAI	L	AIRPO PA				VOR RWY 27		<u>0</u>	ORIGINAL/AN ORIG		K	<u>CITY</u> OTZEBUE		STATE AK
ADDITIONAL FLIGHT	T DATA:														
CHART CIRCLING ICON. CHART OTZ R-115 AT JUMAS. CHART OTZ R-066 AT MUNUE. CHART FAS OBST: 175 BUSH 665354N/1622726W. HOLD SE, RT, 294.60 INBOUND															
MINIMUMS:															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT															
ALTERNATE: NA STANDARD - CAT D 800-2 1/4															
CATEGORY:		Α			В			С		D			E		
FINAL TYPE	DA/MDA	<u>VIS</u>	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	<u>VIS</u>	HAT/HAA	DA/MDA	<u>VIS</u>	HAT/HAA	DA/MDA	<u>VIS</u>	HAT/HAA
S-27	440	1	425	440	1	425	440	1 1/4	425	440	1 1/4	425			
CIRCLING	520	1	505	520	1	505	720	2	705	720	2 1/4	705			
CHANGES - REASONS															

CHAN

- 1. DELETED CHART NOTE DME REQUIRED ADDED EQUIPMENT REQUIREMENT NOTE DME REQUIRED CURRENT CRITERIA.
- 2. UPDATED VGSI REQUIRED NOTE TERMINOLOGY CURRENT CRITERIA.

COORDINATED WITH:

A4A X ALPA X AOPA	X APA HAI	NBAA X OTHE	ER: ZAN, OTZ FSS, AMGR		
FLIGHT CHECKED BY			Digitally signed by OFFICE	DATE	
PROCESSED IAW AIRCRAFT OP SUBJECT: FLIGHT INSPECTION I		MEMO, OCTOBER 3, 2018, Digitally signed by	DAVID DANNER Nov 23, 2018		
DEVELOPED BY		DAVID DANNER	<u>OFFICE</u>	DATE	
LONNIE EVERHART (JOSHUA DL	JGAN)	Nov 23, 2018	AJV-5400		
APPROVED BY	Digitally signed by		<u>OFFICE</u>	DATE	<u>TITLE</u>
LONNIE EVERHART	DAVID DANNER Nov 23, 2018		AJV-5400		MANAGER

^{11 /07/18:} THIS IS A CORRECTED COPY OF THE FORM APPROVED ON 09/28/18.

^{1.} CHANGED CHART NOTE: CIRCLING RWY 9, 18, 36 NA AT NIGHT TO CHART NOTE: CIRCLING RWY 18, 36 NA AT NIGHT.