

**Federal Aviation  
Administration**

**Transmittal Letter 16-14**

**May 20, 2016**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows: .....EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DAT	SUBJECT
23-Jun-16	IL	Springfield	Abraham Lincoln Capital	6/0849	5/5/16	ILS OR LOC RWY 4, Amdt 25F

**AIRAC Date: 23 JUNE 2016**

FDC 6/0849 SPI IAP ABRAHAM LINCOLN CAPITAL, SPRINGFIELD, IL. ILS OR LOC RWY 4, AMDT 25F... S-LOC 4, MDA 1020/HAT 428 ALL CATS, VISIBILITY CAT C/D RVR 4000. CIRCLING CAT A/B MDA 1040/HAA 442, CAT C MDA 1360/HAA 762, CAT D MDA 1380/HAA 782, CAT C VISIBILITY 2 1/4, CAT D VISIBILITY 2 1/2. CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LINCOLN ALTIMETER SETTING AND INCREASE ALL DA 57 FEET, ALL MDA 60FT, INCREASE S-LOC AND CIRCLING CAT C/D VISIBILITY 1/4 MILE. ALTERNATE MINIMUMS: ILS: STANDARD EXCEPT, CAT C 800-2 1/4, CAT D 800-2 1/2, LOC: STANDARD, EXCEPT CAT C 800-2 1/4, CAT D 800-2 1/2. CHART FAS OBST: 761 TWR 394651N/0894410W. CHART CIRCLING ICON. THIS IS ILS OR LOC RWY 4, AMDT 25G. 1603282010-PERM