

<b>US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION</b>	<b>RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33</b>
--	---

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
ODDUB (IAF)	IRCIT (NOPT) (FB)	199.72 / 5.00	4000	LPV: DA LNAV/VNAV: DA LNAV: RW11  CLIMB TO 4000 DIRECT ETSIW AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD E, RT, 290.04 INBOUND. CHART FAS OBST: 1839 TREE 404203N/0762317W FAS OBST: 1939 AAO 404221N/0762730W DISTANCE TO THLD FROM 200 HAT: 0.50 NM. CHART VDP AT 1.35 MILES TO RW11* *LNAV ONLY. WAAS CHANNEL # 61214 REFERENCE PATH ID: W11A
LIXCA (IAF)	IRCIT (NOPT) (FB)	019.70 / 5.00	4000	
IRCIT (IF/IAF)	EHPUZ (FB)	109.71 / 6.09	3400	

1. PT          SIDE OF COURSE          OUTBOUND          FT WITHIN          MILES OF          (IAF)
2. HOLD W IRCIT, RT, 109.71 INBOUND, 4000 FT. IN LIEU OF PT (IAF)
3. FAC: 109.80 FAF: EHPUZ DIST FAF TO MAP: 5.05 THLD: 5.05
4. MIN. ALT: IRCIT 4000, EHPUZ 3400
5. DIST TO THLD FROM OM:          MM:          IM:          150 HAT:          100 HAT:          GS ANT:
6. MIN GS INCPT: 3400 GS ALT AT: EHPUZ 3400 OM:          MM:          IM:
7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS CLEAR
8. MSA FROM:

MAG VAR: 12W                      EPOCH YEAR: 2000

MINIMUMS																	
TAKEOFF:	STANDARD	<input checked="" type="checkbox"/>	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE:	N	A	<input checked="" type="checkbox"/>	<input type="checkbox"/>									
CATEGORY =====>			A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LPV DA	1929	3/4	200	1929	3/4	200	1929	3/4	200	1929	3/4	200					
LNAV/VNAV DA	2109	1 1/4	380	2109	1 1/4	380	2109	1 1/4	380	2109	1 1/4	380					
LNAV MDA	2200	1	471	2200	1	471	2200	1 1/4	471	2200	1 1/2	471					
CIRCLING	2200	1	471	2200	1	471	2200	1 1/2	471	2280	2	551					

NOTES:  
 CHART NOTE: BARO-VNAV NA WHEN USING SELINGSGROVE ALTIMETER SETTING.  
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -18C (0F) OR ABOVE 45C (113F).  
 CHART NOTE: DME/DME RNP-0.3 NA.  
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SELINGSGROVE ALTIMETER SETTING AND SEE 8260-10



CITY AND STATE <b>POTTSVILLE, PA</b>	ELEVATION: 1729 TDZE: 1729 AIRPORT NAME: <b>SCHUYLKILL COUNTY/JOE ZERBEY</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 11, AMDT 2 23 SEP 2010</b>	SUP: AMDT: <b>1</b> DATED <b>08/27/2009</b>
---	--	-------------------------------------	--	---

**RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES CONT.**

INCREASE ALL DA 261 FT AND ALL MDA 280 FT. INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1 MILE, INCREASE LNAV CAT B 1/4 MILE AND CAT C AND CAT D 1 MILE, AND INCREASE CIRCLING CAT B 1/4 MILE AND CAT C AND CAT D 3/4 MILE.

CHART NOTE: VDP NA WHEN USING SELINGSGROVE ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	020/30 CW 200/30 (NOPT)	IRCIT (IF/IAF) (FB)	4000
2.	200/30 CW 290/30	ODDUB (IAF) (FB)	4400
3.	290/30 CW 020/30	LIXCA (IAF) (FB)	4000



CITY AND STATE POTTSVILLE, PA	ELEVATION: 1729 TDZE: 1729	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 11, AMDT 2 23 SEP 2010	SUP:
	AIRPORT NAME: SCHUYLKILL COUNTY/JOE ZERBEY			AMDT: 1
				DATED: 08/27/2009

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION**

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KZER
RUNWAY	RW11
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W11A
LTP/FTP LATITUDE	404223.1515N
LTP/FTP LONGITUDE	0762301.2890W
LTP/FTP ELLIPSOIDAL HEIGHT	+04937
FPAP LATITUDE	404210.9300N
FPAP LONGITUDE	0762105.2400W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1352
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
<b><u>CRC REMAINDER</u></b>	149B4366

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K6
LTP ORTHOMETRIC HEIGHT	+05271
FPAP ORTHOMETRIC HEIGHT	+05271

QUALITY  
 &  
 CHECKED

CITY AND STATE POTTSVILLE, PA	ELEVATION: 1729 TDZE: 1729	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
	AIRPORT NAME: SCHUYLKILL COUNTY/JOE ZERBEY		RNAV (GPS) RWY 11, AMDT 2	AMDT: 1
			23 SEP 2010	DATED: 08/27/2009

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)

1 2 3 4 5 6 7 8 9 0 1 2 3  
WP 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAEAENRT EHPUZ K60 W N40430447W076293599 W0116 NAR EHPUZ  
SUSAEAENRT ETSIW K60 W N40404613W076074989 W0118 NAR ETSIW  
SUSAEAENRT IRCIT K60 W N40435382W076373223 W0115 NAR IRCIT  
SUSAEAENRT LIXCA K60 W N40385634W076382511 W0115 NAR LIXCA  
SUSAEAENRT ODDUB K60 W N40485129W076363922 W0116 NAR ODDUB

1 2 3 4 5 6 7 8 9 0 1 2 3  
AIRPORT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP KZERK6AZER 0 045YHN40422330W07622330W012001729 1800018000C MNAR SCHUYLKILL COUNTY/JOE ZERBEY

1 2 3 4 5 6 7 8 9 0 1 2 3  
SEGMENT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP KZERK6FR11 AIRCIT 010IRCITK6EA0EE AR HF 10970040 + 04000 18000 A JS  
SUSAP KZERK6FR11 ALIXCA 010LIXCAK6EA0E A IF 18000 A JS  
SUSAP KZERK6FR11 ALIXCA 020IRCITK6EA0EE B 010TF 01970050 + 04000 A JS  
SUSAP KZERK6FR11 AODDUB 010ODDUBK6EA0E A IF 18000 A JS  
SUSAP KZERK6FR11 AODDUB 020IRCITK6EA0EE B 010TF 19970050 + 04000 A JS  
SUSAP KZERK6FR11 R 010IRCITK6EA0E I IF 18000 A JS  
SUSAP KZERK6FR11 R 020EHPUZK6EA1E F 051TF 10970061 + 03400 A JS  
SUSAP KZERK6FR11 R 020EHPUZK6EA2WALPV ALNAV/VNAV ALNAV JS  
SUSAP KZERK6FR11 R 030RW11 K6PGOGY M 031TF 10980051 01769 -300 A JS  
SUSAP KZERK6FR11 R 040 0 M 010CA 1098 + 01929 A JS  
SUSAP KZERK6FR11 R 050ETSIWK6EA0EY 010DF + 04000 A JS  
SUSAP KZERK6FR11 R 060ETSIWK6EA0EE R020HM 29000040 + 04000 A JS

1 2 3 4 5 6 7 8 9 0 1 2 3  
RUNWAY 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP KZERK6GRW11 0045991099 N40422315W076230129-0500 +0493701729000040075R

1 2 3 4 5 6 7 8 9 0 1 2 3  
PP 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP KZERK6PR11 RW11 001 0000W11A0N40422315W07623012890+049370300N4042109300W07621052400106751352000400F400350149B4366



CITY AND STATE POTTSVILLE, PA	ELEVATION: 1729 TDZE: 1729 AIRPORT NAME: SCHUYLKILL COUNTY/JOE ZERBEY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 11, AMDT 2 23 SEP 2010	SUP:
				AMDT: 1
				DATED: 08/27/2009

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

1 2 3 4 5 6 7 8 9 0 1 2 3  
 PP 12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012  
 -----  
 SUSAP KZERK6PR11 RW11 002E +05271+05271LPV 61214

QUALITY  
 4  
 CHECKED

CITY AND STATE  
 POTTSVILLE, PA

ELEVATION: 1729 TDZE: 1729  
 AIRPORT NAME:  
 SCHUYLKILL COUNTY/JOE ZERBEY

FACILITY  
 IDENTIFIER:  
 RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
 RNAV (GPS) RWY 11, AMDT 2  
 23 SEP 2010

SUP:	
AMDT:	1
DATED:	08/27/2009