

**Federal Aviation  
Administration**

**Transmittal Letter 18-16**

**June 15, 2018**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBE	FDC DATE	SUBJECT
19-Jul-18	PA	Beaver Falls	Beaver County	8/0984	5/29/18	RNAV (GPS) RWY 10, Orig-B

**AIRAC Date: 19 JULY 2018**

FDC **8/0984** BVI IAP BEAVER COUNTY, Beaver Falls, PA. RNAV (GPS) RWY 10, ORIG-B... LPV DA 1528. LNAV/VNAV DA 1514, LNAV HAT 342 ALL CATS. CHART NOTE: CIRCLING RWY 28 NA AT NIGHT. CHART NOTE: RWY 10 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING PITTSBURGH INTL ALTIMETER SETTING. DELETE NOTE: BARO-VNAV NA WHEN USING PITTSBURGH INTL ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PITTSBURGH INTL ALTIMETER SETTING: INCREASE ALL DA 50 FEET; INCREASE ALL MDAS 60 FEET AND VISIBILITY LNAV CATS C AND D 1/8 SM. DELETE NOTE: WHEN CONTROL TOWER CLOSED, USE PITTSBURGH INTL ALTIMETER SETTING AND INCREASE ALL DA 50 FEET AND ALL MDA 60 FEET; INCREASE LPV ALL CATS VISIBILITY 1/8 MILE, INCREASE LNAV CATS C AND D VISIBILITY 1/4 MILE. DELETE PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ZUTIV ON V115 NORTHEAST BOUND. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. CHART VDP AT 1.05 NM TO RWY10\*  
\*LNAV ONLY. ALTERNATE MINIMUMS: STANDARD. THIS IS RNAV (GPS) RWY 10, ORIG-C. 1805221453-PERM