Federal Aviation Administration

Transmittal Letter 18-16

June 15, 2018

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

AIRAC FDC FDC **STATE** CITY **SUBJECT AIRPORT** DATE **NUMBE** DATE RNAV (GPS) RWY 28, 19-Jul-18 PA Beaver Falls **Beaver County** 8/0985 5/29/18 Orig-B

AIRAC Date: 19 JULY 2018

FDC 8/0985 BVI IAP BEAVER COUNTY, Beaver Falls, PA. RNAV (GPS) RWY 28, ORIG-B... CHART NOTE: CIRCLING RWY 28 NA AT NIGHT. CHART NOTE: RWY 28 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING PITTSBURGH INTL ALTIMETER SETTING, DELETE NOTE: BARO-VNAV NA WHEN USING PITTSBURGH INTL ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED. USE PITTSBURGH INTL ALTIMETER SETTING: INCREASE ALL DA 50 FEET: INCREASE ALL MDAS 60 FEET AND VISIBILITY LNAV CATS C AND D 1/4 SM. DELETE NOTE: WHEN CONTROL TOWER CLOSED, USE PITTSBURGH INTL ALTIMETER SETTING AND INCREASE ALL DA BY 50 FEET AND ALL MDA 60 FEET; INCREASE LNAV/VNAV VISIBILITY 1/8 MILE, INCREASE LNAV CATS C AND D VISIBILITY 1/4 MILE. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. CHART IN PROFILE VIEW: WUBMA/2.50 NM TO RW28 2100* *LNAV ONLY. DELETE IN PROFILE VIEW: WUBMA/2.50 NM TO RW28 2100. CHART VDP AT 1.14 NM TO RW28*. 34:1 IS NOT CLEAR. ALTERNATE MINIMUMS: STANDARD. THIS IS RNAV (GPS) RWY 28, ORIG-C. 1805221453-PERM