

PREPARED BY THE PRODUCT SUPPORT GROUP, AJV-34

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/3/2014	PA	Beaver Falls	Beaver County	4/6371	02/12/14	VOR RWY 28, Amdt 10

FDC **4/6371** BVI IAP BEAVER COUNTY, BEAVER FALLS, PA. VOR RWY 28, AMDT 10... S-28 MDA 2060/HATH 807 ALL CATS. CIRCLING MDA 2060/HAA 807 ALL CATS. MINIMUM ALTITUDE AT ZUDLO EWC 4.5 DME *2060. CHANGE *2100 WHEN USING PITTSBURGH INTL ALTIMETER SETTING PROFILE NOTE TO READ: *2120 WHEN USING PITTSBURGH INTL ALTIMETER SETTING. CHANGE WHEN VGSI INOP NOTE TO READ: PROCEDURE NA AT NIGHT. CHANGE HELICOPTER NOTE TO READ: HELICOPTER VISIBILITY REDUCTION BELOW 1SM NOT AUTHORIZED. CHANGE WHEN CONTROL TOWER CLOSED, USE PITTSBURGH INTL ALTIMETER NOTE TO READ: WHEN CONTROL TOWER CLOSED, USE PITTSBURGH INTL ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET, INCREASE CIRCLING CAT A/D VISIBILITY 1/4 MILE AND INCREASE ZUDLO FIX MINIMUMS S-28 CATS C/D VISIBILITY 1/4 MILE AND CIRCLING CAT C VISIBILITY 1/8 MILE. CHANGE 1656 TOWER TO READ: 1672 TOWER 404807N/0801710W. CHANGE ALL REFERENCE FROM TDZE TO THRE. THIS IS VOR RWY 28, AMDT 10A.