

**Federal Aviation
Administration**

Transmittal Letter 18-16

June 15, 2018

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBE	FDC DATE	SUBJECT
19-Jul-18	PA	Beaver Falls	Beaver County	8/0986	5/29/18	VOR RWY 28, Amdt 10B

AIRAC Date: 19 JULY 2018

FDC **8/0986** BVI IAP BEAVER COUNTY, Beaver Falls, PA. VOR RWY 28, AMDT 10B... DELETE NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: STRAIGHT-IN RWY 28 NA AT NIGHT, CIRCLING RWY 28 NA AT NIGHT. CHART NOTE: RWY 28 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHANGE FINAL STEPDOWN FIX NAME FROM ZUDLO FIX MINIMUMS TO ZUDLO FIX MINIMUMS (DME REQUIRED). CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PITTSBURGH INTL ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET AND VISIBILITY CIRCLING CATS A AND D 1/4 SM AND ZUDLO FIX MINIMUMS S-28 CATS C/D 1/4 SM AND CIRCLING CAT C 1/8 SM. DELETE NOTE: WHEN CONTROL TOWER CLOSED, USE PITTSBURGH INTL ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET, INCREASE CIRCLING CAT A/D VISIBILITY 1/4 MILE AND INCREASE ZUDLO FIX MINIMUMS S-28 CATS C/D VISIBILITY 1/4 MILE AND CIRCLING CAT C VISIBILITY 1/8 MILE. CHANGE ALL REFERENCE FROM EWC VORTAC TO EWC VOR/DME. ALTERNATE MINIMUMS: CAT A/B 900-2, CAT C/D 900-2 1/2. THIS IS VOR RWY 28, AMDT 10C. 1805221454-PERM