# U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and attitudes are in feet MSL. Attitudes are minimum attitudes unless otherwise indicated. Cellings are in feet above airport elevation. Distances are in neutical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, StateAirportEffective DateAmdt. No.PENDER, NEPENDER MUNI26 JULY 2012ORIG

# **TAKEOFF MINIMUMS:**

RWY 33: STANDARD.

RWY 15: 300-1 OR STANDARD WITH A MINIMUM CLIMB OF 213 FT PER NM TO 1700.

#### **TEXTUAL DEPARTURE PROCEDURES:**

## **TAKEOFF OBSTACLE NOTES:**

NOTE: RWY 15, TREES BEGINNING 240 FT FROM DER, 422 FT RIGHT OF CENTERLINE, UP TO 80 FT AGL/1539 FT MSL. TREE 169 FT FROM DER, 425 FT LEFT OF CENTERLINE, 38 FT AGL/1367 FT MSL.

NOTE: RWY 33, TREES AND BUILDING BEGINNING 264 FT FROM DER, 316 FT RIGHT OF CENTERLINE, UP TO 39 FT AGL/1370 FT MSL. TREES BEGINNING 8 FT FROM DER, 318 FT LEFT OF CENTERLINE, UP TO 80 FT AGL/1519 FT MSL.

### **CONTROLLING OBSTACLES:**

Rwy 15: 1539 FT MSL TREE 420514.54N/0964316.27W.

O S