



U.S. Department
of Transportation
Federal Aviation
Administration

DEPARTURE PROCEDURES/TAKEOFF MINIMUMS

Bearings, headings, courses and radials are magnetic. Elevations and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles, except visibilities which are in statute miles or in feet RVR.

COORDINATED WITH →	AAT	ATA	ALPA	AOPA	NBAA	APA	OTHER (Specify) ZKC ARTCC, EMP FSS, ICT FSS, KS STATE AERO
--------------------	-----	-----	------	------	------	-----	--

TAKEOFF MINIMUMS:

RWY 36 - STANDARD

RWY 18 - 600-3 or STANDARD with minimum climb of 345' per NM to 2000

TAKEOFF OBSTACLE:

RWY 18: 1734 Tower 374920/961906

*Concurrent with VOR/DME RWY 18, Original

DEVELOPED BY H		APPROVED BY	
SIGNATURE <i>James J. Kakazu</i>	DATE 4/17/84	SIGNATURE <i>Marc E. Le Wand</i>	DATE 7/25/84
JAMES J. KAKAZU OKC FIFO		MARC E. LE WAND, Manager, OKC FIFO	
CITY AND STATE Eureka, KS	AIRPORT Eureka Muni	EFFECTIVE DATE *	AMDT. NO. Original