U.S. DEPARTMENT of TRANSPORTATION

FEDERAL AVIATION ADMINISTRATION

TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 6, 18, 24, 36 STANDARD.

(2) TEXTUAL DEPARTURE PROCEDURE: RWY 36 - CLIMB HEADING 000.92 TO 1400 BEFORE TURNING RIGHT.

(3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 18, TREE 1506' FROM DER, 809' RIGHT OF CENTERLINE, 100' AGL/989' MSL. NOTE: RWY 36, TREE 1809' FROM DER, 272' RIGHT OF CENTERLINE, 46' AGL/923' MSL.

(4) CONTROLLING OBSTACLES: RWY 36: 1244 MSL TOWER, 385242.00N/0915855.00W

				1
(5) City, State	(6) Airport	(7) Effective Date	(8) Amdt. No.	
FULTON, MO	ELTON HENSLEY MEML	12 MAR 2009	1	Ŷ
		<u></u>	L	s