

U.S. DEPARTMENT of TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

DEPARTURE PROCEDURES / TAKEOFF MINIMUMS

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

COORDINATED

ATA
☐

AAT
☐

ALPA
☐

APA
☒

AOPA
☒

NBAA
☒

OTHER (specify)
☒

ZAB ARTCC, ARPT MGR, FTW FSS

TAKEOFF MINIMUMS:

RWYS 4, 17, 35 STANDARD



RWY 22 - 400 - 2 OR STANDARD WITH MINIMUM CLIMB OF 290 FT PER NM TO 4100.

IFR DEPARTURE PROCEDURE:

TAKEOFF OBSTACLES:

RWY 22 - 4007 TOWER 361953/1020451

DEPARTURE OBSTACLES:

DEVELOPED BY		APPROVED BY	
SIGNATURE:  JIM R. EMORY (NOLAN GLIDEWELL)	DATE: 12/30/97 FIFO: AVN-130	SIGNATURE:  RICK A. WEBB	DATE: FIFO: AVN-130
CITY AND STATE STRATFORD, TX	AIRPORT STRATFORD FIELD	EFFECTIVE 26 MAR 98	AMDT. NO. 4