U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.

Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

 City, State
 Airport
 Effective Date
 Amdt. No.

 TOWANDA, PA
 BRADFORD COUNTY
 26 JULY 2012
 2

TAKEOFF MINIMUMS:

RWY 5 800-2 WITH MINIMUM CLIMB OF 333 FT PER NM TO 2000, OR STANDARD WITH MINIMUM CLIMB OF 461 FT PER NM TO 2000, OR 2000-3 FOR CLIMB IN VISUAL CONDITIONS.

RWY 23 STANDARD WITH MINIMUM CLIMB OF 685 FT PER NM TO 2800, OR 2000-3 FOR CLIMB IN VISUAL CONDITIONS.

TEXTUAL DEPARTURE PROCEDURES:

RWY 5 - CLIMB HEADING 047.03 TO 2000 BEFORE PROCEEDING ON COURSE OR FOR CLIMB IN VISUAL CONDITIONS: CROSS BRADFORD COUNTY AIRPORT AT OR ABOVE 2600 BEFORE PROCEEDING ON COURSE. WHEN EXECUTING VCOA, NOTIFY ATC PRIOR TO DEPARTURE.

RWY 23 - CLIMB HEADING 227.04 TO 2000 BEFORE PROCEEDING ON COURSE OR FOR CLIMB IN VISUAL CONDITIONS: CROSS BRADFORD COUNTY AIRPORT AT OR ABOVE 2600 BEFORE PROCEEDING ON COURSE. WHEN EXECUTING VCOA, NOTIFY ATC PRIOR TO DEPARTURE.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 5, POLE AND TREES BEGINNING 4 FT FROM DER, 267 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/859 FT MSL. GRAIN BIN/SILO AND TREES BEGINNING 131 FT FROM DER, 475 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/823 FT MSL.

NOTE: RWY 23, TREES BEGINNING 1069 FT FROM DER, 1 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/1159 FT MSL. NAVAID 14 FT FROM DER, 113 FT RIGHT OF CENTERLINE, 12 FT AGL/731 FT MSL. TREES BEGINNING 3206 FT FROM DER, 44 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/1287 FT MSL.

CONTROLLING OBSTACLES:

RWY 5: 1319 FT MSL TREES 414621.49N/0762551.12W. 1439 FT MSL TREES 414708.70N/0762433.60W.

RWY 23: 2286 FT MSL TOWER 414104.44N/0762901.12W.

RWY 5/23 (VCOA): 2286 FT MSL TOWER 414104.44N/0762901.12W.

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT:

RWY 05 - 1659 FT MSL AAO 414946.64N/0762410.48W.

RWY 23 - 2286 FT MSL TOWER 414104.44N/0762901.12W.