

TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 6, NA - OBSTACLES.
RWY 24, 600 - 2 WITH MINIMUM CLIMB OF 380 FEET PER NM TO 7,000 OR 3,500 - 3 FOR CLIMB IN VISUAL CONDITIONS.

(2) DEPARTURE PROCEDURE:

RWY 24 - CLIMB HEADING 244 TO 3,300 BEFORE PROCEEDING ON COURSE. FOR CLIMB IN VISUAL CONDITIONS CROSS ELIZABETHTON MUNI AIRPORT AT OR ABOVE 4,900 BEFORE PROCEEDING ON COURSE.

(3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 24, NUMEROUS TREES BEGINNING 1,655' FROM DER, 931' RIGHT OF CENTERLINE, UP TO 100' AGL/2,099' MSL. NUMEROUS TREES 1.36 NM FROM DER, 2,353' LEFT OF CENTERLINE, UP TO 100' AGL/2,179' MSL. POWER LINE 5,898' FROM DER, 973' LEFT OF CENTERLINE, UP TO 200' AGL/1,759' MSL. POWER LINE 1.13 NM DER, 584' RIGHT OF CENTERLINE, UP TO 200' AGL/1,849' MSL.

(4) CONTROLLING OBSTACLES:

RWY 24 (VCOA): 4,159' MSL AAO 362512.11N-0820832.72W, 6,519 MSL AAO 360616.25N-0820720.65W.
RWY 24: 2,305 MSL TOWER 362006.00N-0821256.00W, 6,519 MSL AAO 360616.25N-0820720.65W, 4,424 MSL TOWER 362603.00N-0820802.00W.

(5) City, State
ELIZABETHTON, TN

(6) Airport
ELIZABETHTON MUNI

(7) Effective Date
JUL 5 2007

(8) Amdt. No.
ORIG

