

U.S. Department of Transportation
Federal Aviation Administration

**RNAV-STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
AVUVE WP (IAF)	GIPDI WP (NoPT) (TF) (FB)	075.46/5.00	3000	RW17 CLIMB TO 2000 THEN CLIMBING RIGHT TURN TO 3000 DIRECT GIPDI WP AND HOLD.
EDDIL WP (IAF)	GIPDI WP (NoPT) (TF) (FB)	255.58/5.00	3000	
GIPDI WP	YJJOY WP (TF) (FB)	165.52/5.00	2900	
RW17 (MAP)	GIPDI WP (DF) (FO)		3000	
				ADDITIONAL FLIGHT DATA:
				FAS OBST: 1389 TREE 373750/913551
				YJJOY WP TO RW17: 3.00/40

- PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD N GIPDI WP, RT, 165.50 INBOUND, 3000 FT IN LIEU OF PT (IAF)
- FAC: 165.50 FAF: YJJOY WP DIST FAF TO MAP: THLD: 5.16
- MIN. ALT: GIPDI WP 3000, YJJOY WP 2900
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH:
- MSA FROM:

MIRL RWY 17-35, REIL RWY 17-35

MAG VAR: 2E EPOCH YEAR: 00

MINIMUMS

TAKEOFF:	X	STANDARD	SEE FAA FORM 8260-15 FOR THIS AIRPORT					ALTERNATE: N A		X						
CATEGORY	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV	1740	1	499	1740	1	499		NA			NA					
CIRCLING	1840	1	599	1840	1	599		NA			NA					

NOTES: USE ROLLA NATIONAL ALTIMETER SETTING.

GPS OR RNP-0.3 REQUIRED. DME/DME RNP-0.3 NA

THIS IS A CORRECTED COPY OF A PROCEDURE THAT WAS PUBLISHED IN TL 01-11.

CITY AND STATE	ELEVATION: 1241 TDZE: 1241	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
SALEM, MO	AIRPORT NAME: SALEM MEMORIAL	RNAV	RNAV (GPS) RWY 17, ORIG JUL 12 2001	AMDT: NONE
				DATED

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - FAR PART 97. 33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet. MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FROM	TO	ALTITUDE
1. 346/30 CW 075/30	AVUVE WP (IAF) (FB)	3000
2. 075/30 CW 256/30 (NqPT)	GIPDI WP (IF/IAF) (FB)	3000
3. 256/30 CW 346/30	EDDIL WP (IAF) (FB)	3000

CITY AND STATE SALEM, MO	ELEVATION: 1241 TDZE: 1241	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) JUL 12 2001 RWY 17, ORIG	SUP:
	AIRPORT NAME: SALEM MEMORIAL			AMDT: NONE
				DATED: