Federal Aviation Administration

Transmittal Letter 16-23

September 23, 2016

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10-Nov-16	GA	Americus	Jimmy Carter Rgnl	6/8398	9/20/16	RNAV (GPS) RWY 23, Amdt 1

AIRAC Date: 10 NOVEMBER 2016

FDC 6/8398 ACJ IAP JIMMY CARTER RGNL, AMERICUS, GA. RNAV (GPS) RWY 23, AMDT 1... LPV DA 760 ALL CATS. LNAV/VNAV DA 765 ALL CATS. LNAV HAT 376 ALL CATS, CAT C/D VIS 3/4. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LPV ALL CATS, LNAV/VNAV CAT D, AND LNAV CAT D VISIBILITY TO 1 SM. CHANGE BACKUP ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE COLUMBUS ALTIMETER SETTING AND INCREASE LPV DA TO 874, LNAV/VNAV DA TO 879 AND ALL VISIBILITIES 5/8 SM; INCREASE ALL MDA 120 FEET AND LNAV CATS C AND D VISIBILITY 3/8 SM, AND CIRCLING CAT D VISIBILITY 1/4 SM. CHANGE BACKUP ALTIMETER SETTING INOPERATIVE MALSF NOTE TO READ: FOR INOPERATIVE ALS WHEN USING COLUMBUS ALTIMETER SETTING, INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY TO 1 3/8 SM, LNAV CATS C AND D VISIBILITY TO 1 3/8 SM, AND CIRCLING CAT D VISIBILITY TO 2 1/4 SM. CHART TDZE 464, DELETE THRE 459. DELETE NOTE: WHEN VGSI INOP, CIRCLING RWY 05 NA AT NIGHT. CHART NOTE: CIRCLING RWY 5 NA AT NIGHT. DELETE NOTE: BARO-VNAV NA WHEN USING COLUMBUS ALTIMETER SETTING. DELETE NOTE: VDP NA WITH COLUMBUS ALTIMETER SETTING. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING COLUMBUS ALTIMETER SETTING. DELETE NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: RWY 23 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 23, AMDT 1A. 1608221507-PERM