

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
POCIT	NUCLA (TF) (FB) (RNP 2.00)	003.94 / 17.69	8800
DSD VORTAC	AWBAN (TF) (FO) (RNP 2.00)	097.94 / 20.78	7600
NUCLA (IAF)	AWBAN (NOPT) (TF) (FB) (RNP 1.00)	004.04 / 9.00	7600
FUFQO (IAF)	AWBAN (NOPT) (TF) (FB) (RNP 1.00)	273.03 / 8.29	7600
AWBAN (IF/IAF) (SEE FORM 8260-10)	TISTE (TF) (FB) (RNP 1.00)	288.09 / 6.10	6400

LNAV: RW29

CLIMB TO 4000 THEN CLIMBING RIGHT TURN TO 7000 DIRECT YONKU AND HOLD, CONTINUE CLIMB-IN-HOLD TO 7000.

**ADDITIONAL FLIGHT DATA:
HOLD N, RT, 167.55 INBOUND.
CHART FAS OBST: 3210 TREE 441353N/1210729W.
CHART VDP AT 1.30 NM TO RW29.
TISTE TO RW29: 3.76/43
CHART CIRCLING ICON**

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. **HOLD E AWBAN, RT, 288.09 INBOUND, 7600 FT. IN LIEU OF PT (IAF)**
3. FAC: 288.01 FAF: TISTE DIST FAF TO MAP: 8.20 THLD: 8.20
4. MIN. ALT: **AWBAN 7600, TISTE 6400, HAPET/7.00 NM TO RW29 5920, JEKMO/4.50 NM TO RW29 4900, (SEE FORM 8260-10)**
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: **34:1 IS CLEAR**
8. MSA FROM: **RW29 11600**

MAG VAR: **14E** EPOCH YEAR: **2020**

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD					
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	3560	1	480	3560	1	480	3560	1 3/8	480		NA				
CIRCLING	3560	1	480	3560	1	480	3640	1 1/2	560		NA				

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON DSD VORTAC RADIALS 030 CW 181.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT FUFQO ON V269 EASTBOUND.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT POCIT ON V165 SOUTHEAST BOUND.



CITY AND STATE REDMOND, OR	ELEVATION: 3080 TDZE: 3080 AIRPORT NAME: ROBERTS FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 29, AMDT 2A 1 FEBRUARY 2018	SUP: AMDT: 2 DATED 08/20/2015
--------------------------------------	---	-------------------------------------	---	---

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

LINE 4, (CONT.):
 BODKE/2.00 NM TO RW29 3900

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
TISTE (FAF)	HAPET/7.00 NM TO RW29 (TF) (FB) (RNP 0.30)	288.01 / 1.20	
HAPET/7.00 NM TO RW29	JEKMO/4.50 NM TO RW29 (TF) (FB) (RNP 0.30)	288.01 / 2.50	
JEKMO/4.50 NM TO RW29	BODKE/2.00 NM TO RW29 (TF) (FB) (RNP 0.30)	288.01 / 2.50	
BODKE/2.00 NM TO RW29	RW29 (MAP) (TF) (FO) (RNP 0.30)	288.01 / 2.00	
RW29 (MAP)	4000 MSL (CA)	288.01	4000
4000 MSL	YONKU (DF) (FO) (RNP 1.00)		7000



CITY AND STATE REDMOND, OR	ELEVATION: 3080 AIRPORT NAME: ROBERTS FIELD	TDZE: 3080	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 29, AMDT 2A 1 FEBRUARY 2018	SUP:
					AMDT: 2
					DATED: 08/20/2015