

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97. 23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: PVD 0.64 DME						
PVD VORTAC		BRIGG / PVD 7.00 DME			053.00 / 7.00			2100		CLIMBING RIGHT TURN TO 2500 VIA PVD R-321 TO FOSTY INT AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, LT, 057 INBOUND. FAS OBST: 152 CROSS 414343/0712425 424 TWRS 414652/0711952. FAC CROSSES RWY C/L EXTENDED 3609 FEET FROM RWY THR. CHART VDP AT 1.70 DME, DISTANCE VDP TO THR 1.18 MILES. BRIGG TO RW23: 2.91 / 55						
1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF) 2. HOLD NE BRIGG / PVD 7.00 DME, LT, 233 INBOUND, 2100 FT. IN LIEU OF PT. (IAF) 3. FAC 233.00 FAF BRIGG DIST FAF TO MAP - THLD 6.47 4. MIN. ALT BRIGG 2100, PVD 4.00 DME 1100 5. MSA FROM: PVD VORTAC 2600.										MAG VAR: 14W EPOCH YEAR: 65						
MINIMUMS																
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD				
CATEGORY ==>		A			B			C			D			E		
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-23		440	4000	390	440	4000	390	440	4000	390	440	6000	390			
CIRCLING		560	1	505	560	1	505	580	1 1/2	525	620	2	565			
NOTES: FOR INOPERATIVE MALSR INCREASE S-23 CATS A, B, & C VISIBILITY TO RVR 5000, CAT D VISIBILITY TO RVR 6000.																
CITY AND STATE				ELEVATION: 55 TDZE: 50		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP				
PROVICENCE, RI				THEODORE FRANCIS GREEN STATE		PNVD		JUL 10 2003 VOR/DME RWY 23, AMDT 6E				AMDT 6D				
												DATE 08/09/01				