FEDERAL AVIATION ADMINISTRATION

FLIGHT STANDARDS SERVICE

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE

TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.

Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

AIRPORTAIRPORT IDPROCEDURE NAMEORIGINAL/AMENDMENTCITYSTATEKELLER BROTHERSK08NRNAV (GPS) RWY 25ORIG-BLEBANONPA

 AIRPORT ELEVATION
 TDZE
 SUPERSEDED
 ORIGINAL/AMENDMENT
 DATED
 MAG VAR
 EPOCH YEAR

 550
 547
 RNAV (GPS) RWY 25
 ORIG-A
 06/22/2017
 12W
 2010

FACILITY COORDINATES OF FACILITIES ACTUAL EFFECTIVE DATE RNAV 3 JANUARY 2019 ROUTINE CANCEL/SUSPEND

TERMINAL ROUTES

FROM	FIX TYPE	<u>TO</u>	FIX TYPE	LEG TYPE	FO/FB	RNP	<u>COURSE</u>	DISTANCE	ALTITUDE
DUMMR	IF/IAF	YAPSU		TF	FB	1.00	228.13	9.63	2200
YAPSU	FAF	RW25	MAP	TF	FO	0.30	248.11	5.10	
RW25	MAP	950 MSL		CA			248.11		
950 MSL		BAARN		DF	FO	1.00			3000

MISSED APPROACH

MAP:

LNAV: RW25

MISSED APPROACH INSTRUCTIONS:

CLIMBING RIGHT TURN TO 3000 DIRECT BAARN AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)

2. PROFILE STARTS AT DUMMR

3. FAC: 248.11 **FAF**: YAPSU **DIST FAF TO MAP**: 5.10 **DIST FAF TO THLD**: 5.10

4. MIN ALT: DUMMR 4000, YAPSU 2200

5. DIST TO THLD FROM OM: MM: IM: 150 HAT: GS ANT:

6. MIN GP INCPT: GP ALT AT FAF: OM: MM: IM:

7. GP ANGLE: 34:1: IS NOT CLEAR 20:1: IS NOT CLEAR TCH:

8. MSA FROM: RW25 3100

PBN REQUIREMENTS NOTE:

RNP APCH.



AIRPORT AIRPORT ID PROCEDURE NAME ORIGINAL/AMENDMENT CITY STATE
KELLER BROTHERS K08N RNAV (GPS) RWY 25 ORIG-B LEBANON PA

NOTES:

CHART NOTE: PROCEDURE NA AT NIGHT.

CHART NOTE: RWY 7 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT DUMMR ON V93 NORTHEAST BOUND, V162 EASTBOUND AND V276 SOUTHEAST BOUND.

CHART NOTE: USE LANCASTER ALTIMETER SETTING; WHEN NOT RECEIVED, USE READING ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET AND CIRCLING CAT B VISIBILITY 1/4 MILE.

ADDITIONAL FLIGHT DATA:

CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES.

CHART LANCASTER ASOS FREQUENCY. FAS OBST: 1019 AAO 401831N/0761622W. HOLD E, LT, 256.02 INBOUND

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA χ

CATEGORY:	A		В		С			D			E				
FINAL TYPE	DA/MDA	<u>VIS</u>	HAT/HAA												
LNAV MDA	1320	1	773	1320	1 1/4	773		NA			NA				
CIRCLING	1440	1 1/4	890	1480	1 1/4	930		NA			NA				

CHANGES - REASONS

- 1. ADDED 20:1 IS NOT CLEAR ON LINE 7 IAW CURRENT 8260.19 CRITERIA.
- 2. REMOVED CHART NOTE "DME/DME RNP 0.3 NA" CHANGED TO PBN REQUIREMENT NOTE "RNP APCH" IAW CURRENT 8260.19 CRITERIA.
- 3. ADDED PBN REQUIREMENT NOTE "RNP APCH" IAW CURRENT 8260.19 CRITERIA.
- 4. REMOVED "YAPSU TO RW25: 3.00/40" FROM ADDITIONAL FLIGHT DATA PER FLIGHT CHECK REQUEST
- 5. ADDED CHART PROFILE NOTE "VISUAL SEGMENT OBSTACLES" TO ADDITIONAL FLIGHT DATA IAW CURRENT 8260.19 CRITERIA: VDA REMOVED.
- 6. CHANGED CHART NOTE FROM "RWY 7, 25 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED" TO "RWY 7 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED" NOTE ONLY APPLIES TO STRAIGHT-IN PORTION IAW CURRENT 8260.19 CRITERIA.

COORDINATED WITH: A4A ALPA AOPA X APA HAI NBAA X **OTHER:** MDT APP CON, ZNY, AIRPORT MANAGER. **FLIGHT CHECKED BY OFFICE DATE** Digitally signed by **ROBERT G HAMILTON** FLIGHT INSPECTION REVIEW NOT REQUIRED - PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-33) MEMO, DEC 22, 2017. Sep 21, 2018 **DEVELOPED BY OFFICE DATE** Digitally signed by **DUSTIN DAVIDSON DUSTIN DAVIDSON** AJV-5422 07/20/2018 Sep 14, 2018 **APPROVED BY OFFICE DATE TITLE** JULIE MORGAN AJV-5420 MANAGER Digitally signed by **ROBERT G HAMILTON** Sep 21, 2018

PROCEDURE NAME

RNAV (GPS) RWY 25

AIRPORT

KELLER BROTHERS

AIRPORT ID

K08N

CITY

LEBANON

STATE

PΑ

ORIGINAL/AMENDMENT

ORIG-B