

TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 18, 36: STANDARD

NOTE: RWY 36 CROSS DER AT OR ABOVE 16 FEET AGL/461 FEET MSL

(2) TEXTUAL DP:

RWY 18: CLIMB RUNWAY HEADING TO 2500 BEFORE TURNING ON COURSE

RWY 36: CLIMB RUNWAY HEADING TO 2800 BEFORE TURNING ON COURSE

(3) TAKEOFF OBSTACLES:

(4) OBSTACLES:

**RWY 18: 2575 MSL TOWER 350408/944115
2645 MSL TOWER 350410/944114
2650 MSL TOWER 350113/942806
2645 MSL TOWER 350419/944047**

**RWY 36: 2515 MSL TOWER 350421/940442
2645 MSL TOWER 350419/944047
2650 MSL TOWER 350131/942806**

(5) City, State

POTEAU, OK

(6) Airport

ROBERT S. KERR

(7) Effective Date

OCT 3 2002

(8) Amdt. No.

4