

**Federal Aviation
Administration**

Transmittal Letter 09-25

October 30, 2009

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

17-Dec-09	SD	Huron	Huron Regional	9/2314	10-23-09	RNAV (GPS) RWY 30, Amdt 1
-----------	----	-------	----------------	--------	----------	------------------------------

AIRAC Date: 17 DECEMBER 2009

FDC 9/2314 HON FI/P HURON REGIONAL, HURON, SD. RNAV (GPS) RWY 30, AMDT 1...LPV DA 1559/HAT 273 ALL CATS. LNAV/VNAV DA 1721/HAT 435 ALL CATS. CIRCLING CATS A/B VISIBILITY 1. DELETE NOTE: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE MITCHELL MUNI ALTIMETER SETTING AND INCREASE ALL DAS/MDAS 100 FEET. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MITCHELL MUNI ALTIMETER SETTING AND INCREASE ALL DA 89 FEET AND ALL MDA 100 FEET, INCREASE LPV AND LNAV/VNAV ALL CATS, LNAV CATS C/D, AND CIRCLING CATS C/D VISIBILITY 1/4 MILE. DELETE NOTE: BARO-VNAV NA BELOW -18C (0F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2 F) OR ABOVE 46C (114F). DIST TO THLD FROM 273 HAT: .71NM DELETE VDP AT 1.3 MILES TO RWY 30 (ASTERISK) LNAV ONLY. DELETE NOTE: BARO-VNAV AND VDP NA WHEN USING MITCHELL MUNI ALTIMETER SETTING. CHART NOTE: BARO-VNAV NA WHEN USING MITCHELL MUNI ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 30, AMDT 1A.