

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> AMERY MUNI	<u>AIRPORT ID</u> KAHH	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 18	<u>ORIGINAL/AMENDMENT</u> 1B	<u>CITY</u> AMERY	<u>STATE</u> WI	
<u>AIRPORT ELEVATION</u> 1088	<u>TDZE</u> 1080	<u>SUPERSEDED</u> RNAV (GPS) RWY 18	<u>ORIGINAL/AMENDMENT</u> 1A	<u>DATED</u> 04/02/2015	<u>MAG VAR</u> 1E	<u>EPOCH YEAR</u> 2005
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 5 DECEMBER 2019	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
AGUDE		JANIL		TF	FO	1.00	000.06	20.44	3000
ALEEN	IAF	JANIL	NOPT	TF	FB	1.00	207.44	13.77	3000
JANIL	IF/IAF	EBAYI		TF	FB	1.00	177.36	6.03	2700
EBAYI	FAF	UHVAG/1.80 NM TO RW18		TF	FB	0.30	177.38	3.17	
UHVAG/1.80 NM TO RW18		RW18	MAP	TF	FO	0.30	177.38	1.80	
RW18	MAP	1488 MSL		CA			177.38		
1488 MSL		FISOM		DF	FO	1.00			3000

MISSED APPROACH

MAP:

LP: RW18
LNAV: RW18

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 3000 DIRECT FISOM AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF (IAF)

2. HOLD N JANIL, RT, 177.36 INBOUND, 3000 FT. IN LIEU OF PT (IAF), MAX 6000.

3. FAC: 177.38FAF: EBAYIDIST FAF TO MAP: 4.97DIST FAF TO THLD: 4.97

4. MIN ALT: JANIL 3000, EBAYI 2700, UHVAG/1.80 NM TO RW18 1680

5. DIST TO THLD FROM OM:MM:IM:150 HAT:GS ANT:MM:IM:

6. MIN GP INCPT:GP ALT AT FAF :OM:

7. GP ANGLE:34:1: IS NOT CLEAR20:1: IS CLEARTCH:

8. MSA FROM: RW18 3200

PBN REQUIREMENTS NOTE:

RNP APCH.

NOTES:

CHART NOTE: RWY 18 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.
CHART NOTE: USE NEW RICHMOND ALTIMETER SETTING; WHEN NOT RECEIVED, USE OSCEOLA ALTIMETER SETTING AND INCREASE ALL MDAS 20 FEET AND CIRCLING CAT C VISIBILITY 1/4 SM.

ADDITIONAL FLIGHT DATA:

CHART CIRCLING ICON
CHART NEW RICHMOND AWOS-3
CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES.
WAAS CHANNEL #77732
REFERENCE PATH ID: W18A
CHART FAS OBST: 1194 TREE 451751N/0922244W, 1219 WATER_TOWER 451752N/0922150W.
HOLD S, RT, 357.37 INBOUND
LTP HAE: 299.1 M

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☒

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LP MDA	1500	1	420	1500	1	420	1500	1 1/4	420		NA				
LNAV MDA	1600	1	520	1600	1	520	1600	1 1/2	520		NA				
CIRCLING	1740	1	652	1740	1	652	1740	1 3/4	652		NA				



FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KAHH
RUNWAY	RW18
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W18A
LTP/FTP LATITUDE	451711.8725N
LTP/FTP LONGITUDE	0922232.2025W
LTP/FTP ELLIPSOIDAL HEIGHT	+02991
FPAP LATITUDE	451542.8200N
FPAP LONGITUDE	0922228.6300W
THRESHOLD CROSSING HEIGHT (TCH)	00000.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	00.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1528
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0
CRC REMAINDER	6C1E8233

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+03285
FPAP ORTHOMETRIC HEIGHT	+03285

