FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP) TITLE 14 CER PART 97 37

TITLE 14 CFR PART 97.37

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL Altitudes are minimum altitudes unless otherwise indicated

CITY, STATEAIRPORTEFFECTIVE DATEAMDT NOWATERVILLE, MEWATERVILLE ROBERT LAFLEUR8 NOVEMBER 20181

Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

TAKEOFF MINIMUMS:

RWY 5, 14, 23: STANDARD.

RWY 32: STANDARD WITH MINIMUM CLIMB OF 375 FT TO 700, OR 1000 - 2 1/2 FOR VCOA.

TEXTUAL DEPARTURE PROCEDURES:

VISUAL CLIMB OVER AIRPORT:

RWY 32: OBTAIN ATC APPROVAL FOR VCOA WHEN REQUESTING IFR CLEARANCE. CLIMB IN VISUAL CONDITIONS TO CROSS WATERVILLE ROBERT LAFLEUR AIRPORT AT OR ABOVE 1100 BEFORE PROCEEDING ON COURSE.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 05: TREE 615 FT FROM DER, 572 FT RIGHT OF CENTERLINE, 66 FT AGL/358 FT MSL. TREE 1201 FT FROM DER, 616 FT LEFT OF CENTERLINE. 57 FT AGL/366 FT MSL.

NOTE: RWY 14: TREE 215 FT FROM DER, 292 FT RIGHT OF CENTERLINE, 41 FT AGL/333 FT MSL. TREE 238 FT FROM DER, 296 FT LEFT OF CENTERLINE, 42 FT AGL/333 FT MSL. TREE 249 FT FROM DER, 509 FT LEFT OF CENTERLINE, 77 FT AGL/371 FT MSL. TREES BEGINNING 264 FT FROM DER, 257 FT RIGHT OF CENTERLINE, UP TO 63 FT AGL/351 FT MSL.

NOTE: RWY 32: TREE 590 FT FROM DER, 234 FT RIGHT OF CENTERLINE, 67 FT AGL/334 FT MSL. TREE 634 FT FROM DER, 134 FT LEFT OF CENTERLINE, 73 FT AGL/340 FT MSL. TREE, BUILDING BEGINNING 2121 FT FROM DER, 144 FT LEFT OF CENTERLINE, UP TO 82 FT AGL/419 FT MSL. BUILDING 3054 FT FROM DER, 585 FT LEFT OF CENTERLINE, 30 FT AGL/430 FT MSL. TANK 3618 FT FROM DER, 656 FT RIGHT OF CENTERLINE, 67 FT AGL/477 FT MSL. TREE 5420 FT FROM DER, 1044 FT LEFT OF CENTERLINE, 90 FT AGL/549 FT MSL.

CONTROLLING OBSTACLES:

RWY 32: 477 FT MSL TANK 443233.13N/0694119.77W (CG), 549 FT MSL TREE 443229.67N/0694153.65W (CGTA).

RWY 32 (VCOA): 759 FT MSL TOWER 443316.08N/0694427.01W.

REMARKS:

Digitally signed by

FLIGHT INSPECTED BY: ROBERT G HAMILTON

Sep 14, 2018

FICO

DATE:
9/12/18

RUSSELL P ELLIOTT FICO

 Digitally signed by
 DEVELOPED BY:
 DAVID A DOWLING
 OFFICE SYMBOL: AJV-5422
 DATE: 06/06/2018

 DAVID DOWLING
 Aug 14, 2018
 AJV-5422
 06/06/2018

APPROVED BY: Digitally signed by OFFICE SYMBOL: DATE:

ROBERT G HAMILTON AJV-5420

JULIE MORGAN
Sep 14, 2018

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

A4A ALPA AOPA APA HAI NBAA

OTHER:

AMGR, PORTLAND APP CON, EASTERN FPT, ZBW

CHANGES - REASONS:

RWY 32 TAKEOFF MINIMUMS: CHANGED FROM 300-1 TO STANDARD WITH MINIMUM CLIMB OF 375 FT PER NM TO 700 - NEW OBSTACLE EVALUATION..

RWY 32 TAKEOFF MINIMUMS: ADDED VCOA CEILING AND VISIBILITY - IFR DEPARTURE OPTION FOR LOWER PERFORMANCE AIRCRAFT.

RWY 14 TAKEOFF MINIMUMS: CHANGED FROM 300-1 TO STANDARD - NEW OBSTACLE EVALUATION.

RWY 5, 14, 32 TAKEOFF OBSTACLES: NEW OBSTACLES THROUGHOUT - NEW EVALUATION.

RWY 32 CONTROLLING OBSTACLES: ADDED FOR CLIMB GRADIENT, CLIMB GRADIENT TERMINATION ALTITUDE, AND VCOA - NEW EVALUATION.