

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW19
OCF VORTAC (IAF)	FRINC (FB)	202.55 / 12.53	2000	CLIMB TO 2000 DIRECT BOWSK AND ON TRACK 175.80 TO REBEC AND HOLD.
VANNI (IAF)	FRINC (FB)	247.99 / 10.00	2000	
FRINC (IF)	GIOVA (FB)	190.81 / 5.00	1700	
GIOVA (FAF)	RW19 (MAP) (FO)	190.80 / 5.07		
RW19 (MAP)	465 MSL	190.80		ADDITIONAL FLIGHT DATA: HOLD S, RT, 340.82 INBOUND. CHART FAS OBST: 279 TOWER 284933N/0821911W GIOVA TO RW19: 3.00/46.
465 MSL	BOWSK (FB)			
BOWSK	REBEC (FO)	175.80 / 9.66	2000	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- PROFILE STARTS AT FRINC
- FAC: 190.80 FAF: GIOVA DIST FAF TO MAP: 5.07 THLD: 5.07
- MIN. ALT: FRINC 2000, GIOVA 1700
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM: RW19 1800

MAG VAR: 5W

EPOCH YEAR: 2010

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	580	1	539	580	1	539	580	1 1/2	539		NA				
CIRCLING	660	1	595	660	1	595	660	1 1/2	595		NA				

NOTES:
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE OCALA ALTIMETER SETTING AND INCREASE ALL MDA 60 FT; AND INCREASE LNAV AND CIRCLING CAT C VISIBILITY 1/4 MILE.
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 (SEE FORM 8260-10)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
CHECKED

CITY AND STATE INVERNESS, FL	ELEVATION: 65 THRE: 41 AIRPORT NAME: INVERNESS	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, ORIG 5 APR 2012	SUP:
				AMDT: NONE
				DATED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33


Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON OCF VORTAC AIRWAY RADIALS 129 CW 208.

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.

CHART NOTE: PROCEDURE NA AT NIGHT.



CITY AND STATE INVERNESS, FL	ELEVATION: 65	THRE: 41	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, ORIG 5 APR 2012	SUP:
	AIRPORT NAME: INVERNESS	AMDT: NONE			
	DATED:				

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KINFK7FR19	AOCF	010OCF	K7D	0V	A	IF				18000		B	JS
SUSAP KINFK7FR19	AOCF	020FRINCK7EA0EE	B	010TF			20260125	+	02000			B	JS
SUSAP KINFK7FR19	AVANNI	010VANNIK7EA0E	A	IF						18000		B	JS
SUSAP KINFK7FR19	AVANNI	020FRINCK7EA0EE	B	010TF			24800100	+	02000			B	JS
SUSAP KINFK7FR19	R	010FRINCK7EA0E	I	IF				+	02000	18000		B	JS
SUSAP KINFK7FR19	R	020GIOVAK7EA1E	F	051TF			19080050	+	01700		RW19	K7PGB	JS
SUSAP KINFK7FR19	R	020GIOVAK7EA2WN			N	ALNAV							JS
SUSAP KINFK7FR19	R	030RW19	K7FGOGY	M	031TF		19080051		00087	-300		B	JS
SUSAP KINFK7FR19	R	040	0	M	CA		1908	+	00465			B	JS
SUSAP KINFK7FR19	R	050BOWSKK7EA0E		DF								B	JS
SUSAP KINFK7FR19	R	060REBECK7EA0EY		010TF			1758	+	02000			B	JS
SUSAP KINFK7FR19	R	070REBECK7EA0EE	R	HM			34080040	+	02000			B	JS

[illegible][illegible]

SUP:	
AMDT:	NONE
DATED:	

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-8 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	OCF	OCF	010	IAF	IF		FB					
	OCF	FRINC	020		TF		FB	1.0	202.6(197.6T)	012.5	AA 02000	
	VANNI	VANNI	010	IAF	IF		FB					
	VANNI	FRINC	020		TF		FB	1.0	248.0(243.0T)	010.0	AA 02000	
		FRINC	010	FACF	IF		FB				AA 02000	
		GIOVA	020	FAF	TF		FB	0.5	190.8(185.8T)	005.0	AA 01700	
		RW19	030	MAP	TF		FO	0.3	190.8(185.8T)	005.1	AT 00087	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		190.8(185.8T)		AA 00465	
	BOWSK	050		DF		FB					
	REBEC	060		TF		FO	1.0	175.8(170.8T)		AA 02000	
	REBEC	070		HM	R	FO		340.8(335.8T)	004.0	AA 02000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	OCF	N291038.92	W0821334.80	N2910.649	W08213.580
	BOWSK	N284249.88	W0821942.93	N2842.831	W08219.716
	FRINC	N285840.27	W0821753.23	N2858.671	W08217.887
	GIOVA	N285340.85	W0821827.85	N2853.681	W08218.464
	REBEC	N283316.14	W0821757.71	N2833.269	W08217.962
	VANNI	N290313.86	W0820743.78	N2903.231	W08207.730
	RW19	N284837.62	W0821902.85	N2848.627	W08219.048

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW19	00041	46

QUALITY
4
CHECKED

CITY AND STATE INVERNESS, FL	ELEVATION: 65	THRE: 41	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:	INVERNESS	RNAV	RNAV (GPS) RWY 19, ORIG	AMDT: NONE
				5 APR 2012	DATED: