

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
LUISS (IAF)	FLUBS (NOPT) (TF) (FB) ← (RNP 1.00)	149.87 / 13.21	13400
FLUBS	ICORY (TF) (FB) (RNP 1.00)	151.67 / 13.21	11100
HOMME (IAF)	ICORY (NOPT) (TF) (FB) (RNP 1.00)	330.95 / 18.50	11100
ICORY (IF/IAF)	ZINGS (TF) (FB) (RNP 1.00)	241.59 / 10.68	9500
ZINGS (FAF)	RW24 (MAP) (TF) (FO) (RNP 0.30)	239.52 / 4.90	

(SEE FORM 8260-10)

THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 17-21.

LPV: DA
LNAV/VNAV: DA
LNAV: RW24

CLIMB TO 8600 THEN CLIMBING LEFT TURN TO 11100 DIRECT SHERN AND ON TRACK 150.94 TO HOMME AND HOLD. ~~MISSED~~ APPROACH REQUIRES A MINIMUM CLIMB OF 310 FEET PER NM TO 9200.

ADDITIONAL FLIGHT DATA:
HOLD NW, RT, 150.94 INBOUND.
CHART FAS OBST: 8219 TREE 374342N/1062006W
DISTANCE TO THLD FROM 250 HAT: 0.62 NM.
CHART VDP AT 2.34 NM TO RW24*
*LNAV ONLY.
WAAS CHANNEL # 93740
REFERENCE PATH ID: W24A
CHART CIRCLING ICON.
LTP HAE: 2388.6 M

MAG VAR: 8E EPOCH YEAR: 2020

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD NE ICORY, RT, 241.59 INBOUND, 11100 FT. IN LIEU OF PT (IAF)
3. FAC: 239.52 FAF: ZINGS DIST FAF TO MAP: 4.90 THLD: 4.90
4. MIN. ALT: ICORY 11100, ZINGS 9500
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: 9500 GS ALT AT: ZINGS 9500 OM: MM: IM:
7. GS ANGLE: 3.00 TCH: 51.0 34:1 IS CLEAR
8. MSA FROM: RW24 15100

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A	STANDARD @								
CATEGORY =====>	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA ** ←	8163	1	250	8163	1	250		NA			NA					
LPV DA	8220	1 1/8	307	8220	1 1/8	307		NA			NA					
LNAV/VNAV DA	8443	1 7/8	530	8443	1 7/8	530		NA			NA					
LNAV MDA	8680	1	767	8680	1 1/4	767		NA			NA					
CIRCLING	8700	1	745	8840	1 1/4	885		NA			NA					

NOTES:
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -30C (-22F) OR ABOVE 54C (130F). @ CAT B 900-2
 CHART NOTE: CIRCLING NA NW OF RWY 06-24.
 CHART NOTE: CIRCLING RWY 06 NA AT NIGHT.
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). ←



CITY AND STATE DEL NORTE, CO	ELEVATION: 7955 TDZE: 7913 AIRPORT NAME: ASTRONAUT KENT ROMINGER	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 24, ORIG 12 OCTOBER 2017	SUP: AMDT: NONE DATED
---------------------------------	-----------------------------------------------------------------------------	------------------------------	--------------------------------------------------------------------------------------	-----------------------------

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
RW24 (MAP)	8600 MSL (CA)	239.52	8600
8600 MSL	SHERN (DF) (RNP 1.00)		
SHERN	HOMME (TF) (FO) (RNP 1.00)	150.94/13.00	11100



CITY AND STATE DEL NORTE, CO	ELEVATION: 7955 TDZE: 7913 AIRPORT NAME: ASTRONAUT KENT ROMINGER	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 24, ORIG 12 OCTOBER 2017	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KRCV
RUNWAY	RW24
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W24A
LTP/FTP LATITUDE	374253.7535N
LTP/FTP LONGITUDE	1062035.2390W
LTP/FTP ELLIPSOIDAL HEIGHT	+23886
FPAP LATITUDE	374219.5470N
FPAP LONGITUDE	1062218.9380W
THRESHOLD CROSSING HEIGHT (TCH)	00051.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0904
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER C7354870

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+24048
FPAP ORTHOMETRIC HEIGHT	+24048



CITY AND STATE DEL NORTE, CO	ELEVATION: 7955	TDZE: 7913	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 24, ORIG 12 OCTOBER 2017	SUP:
	AIRPORT NAME: ASTRONAUT KENT ROMINGER				AMDT: NONE
					DATED: